



**PROPULSE<sup>®</sup>**  
A SCHIEFFER CO.

***POWER MOVING FORWARD<sup>™</sup>***





PRODUCTS THAT STRENGTHEN YOUR  
POWER MOVING  
FORWARD





## INTRODUCING THE NEW “PROPULSE NOW!” CATALOG.

We stock over 150 of the most widely used hose assemblies for six vertical markets: commercial cleaning, consumer cleaning, carpet cleaning, carwash cleaning, sewer jetting and drain cleaning. As an added effort to provide value and service to our customers, we have structured pricing based on revenue and quantity commitments to ProPulse®.

### With ProPulse Now! you can enjoy the convenience of:

- › Shipment within 24 hours (often same day) on inventory in stock
- › Industry standard products for high pressure cleaning applications
- › Industry exclusive patent pending products
- › Customized products available based on annual sales commitments to ProPulse
- › Access to discounts based on annual sales and volume purchases

### ORDER THESE INNOVATIVE PRODUCTS TODAY.

**PHONE** 563.583.4758

**TOLL-FREE** 877.384.4673

**FAX** 800.303.4673

**EMAIL** [info@powermovingforward.com](mailto:info@powermovingforward.com)

**[www.PowerMovingForward.com](http://www.PowerMovingForward.com)**





# PROPULSE COMMERCIAL CLEANSTREAM™



The latest technology from ProPulse and a revolutionary upgrade from the standard farm and commercial duty gasoline and electric cold water pressure washer hose. CLEANSTREAM™ hoses are U.S. patent pending and possess the unique properties of lightweight, ultraviolet light (UV) and ozone resistance and superior flexibility. A textured high abrasion resistant cover, stability in length and true non-marking cover add to the overall ease of handling.

- › Suitable for consumer and commercial pressure cleaning applications
- › Reinforcement: One layer of high tensile braided steel
- › Cover: Textured matte finish with printed lay line
- › Inner Diameter: 5/16" and 3/8"
- › Working (Maximum): Up to 4000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 140°F
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more
- › **Not for hot water or steam**

# COMMERCIAL CLEANSTREAM™

## HOSE CONSTRUCTION:

- › Inner Tube: Water and chemical resistant polyester and polyurethane
- › Reinforcement: One layer of high tensile braided steel
- › Cover: Matte finish TPU provides a lower coefficient of friction
- › Laminated: Bonded construction for long life

**MADE IN USA:** Every foot of ProPulse CLEANSTREAM is designed, engineered and manufactured in the USA, assembled using imported and/or domestic end fittings.

## UNMATCHED ABRASION, OZONE, UV AND

**CHEMICAL RESISTANCE:** The proprietary, high performance, CLEANSTREAM cover is at least five times more abrasion resistant than equivalent rubber hoses and also eliminates cracking caused by exposure to UV, ozone and chemical exposure, a common weakness for standard rubber hoses.

**NO PINHOLES:** The ProPulse CLEANSTREAM utilizes a special inner tube that reduces the probability of pinholes inherent in equivalent mandrel-built rubber hoses.

**TEMPERATURE RANGE:** For water up to 140°F (71°C).

**FLEXIBLE:** Highly flexible materials result in a dynamic bend radius for CLEANSTREAM equivalent or better than wire braided rubber hoses, especially in cold weather.

**CLEANLINESS:** ProPulse's special manufacturing process effectively eliminates inner contamination, which is an inherent byproduct of rubber hose manufacturing processes. The inner tube will not erode, ensuring long term cleanliness.

**FLOW THROUGH:** Super smooth inner tube is designed for less pressure loss for increased performance and efficiency at the nozzle.

**KINK AND CUT RESISTANCE:** High tensile strength steel wire braiding ensures cut-through and kink resistance just like standard rubber hoses and is much better than textile yarn reinforced hoses such as SAE100R7.

**COLOR MATCH:** Cover color optional with volume.

**LIGHTWEIGHT:** Efficient material usage reduces overall weight by up to 30% when compared to equivalent hoses.

*Specifications are preliminary and subject to change.*

### 5/16" 4000 PSI CLEANSTREAM GREY (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400028	HYBD HS 5/16"x25' 4000PSI GREY CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400029	HYBD HS 5/16"x50' 4000PSI GREY CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400030	HYBD HS 5/16"x100' 4000PSI GREY CLEANSTREAM 3/8"SOLx3/8"SWV 2BR

### 5/16" 4000 PSI CLEANSTREAM BLACK (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400022	HYBD HS 5/16"x25' 4000PSI BLACK CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400023	HYBD HS 5/16"x50' 4000PSI BLACK CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400024	HYBD HS 5/16"x100' 4000PSI BLACK CLEANSTREAM 3/8"SOLx3/8"SWV 2BR

### 5/16" 4000 PSI CLEANSTREAM BLUE (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400025	HYBD HS 5/16"x25' 4000PSI BLUE CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400026	HYBD HS 5/16"x50' 4000PSI BLUE CLEANSTREAM 3/8"SOLx3/8"SWV 2BR
489400027	HYBD HS 5/16"x100' 4000PSI BLUE CLEANSTREAM 3/8"SOLx3/8"SWV 2BR

### 3/8" 4000 PSI CLEANSTREAM GREY (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400007	HYBD HS 3/8"x25' 4000PSI GREY CLEANSTREAM SOLxSWV 2BR
489400008	HYBD HS 3/8"x50' 4000PSI GREY CLEANSTREAM SOLxSWV 2BR
489400009	HYBD HS 3/8"x100' 4000PSI GREY CLEANSTREAM SOLxSWV 2BR

### 3/8" 4000 PSI CLEANSTREAM BLACK (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400010	HYBD HS 3/8"x25' 4000PSI BLACK CLEANSTREAM SOLxSWV 2BR
489400011	HYBD HS 3/8"x50' 4000PSI BLACK CLEANSTREAM SOLxSWV 2BR
489400012	HYBD HS 3/8"x100' 4000PSI BLACK CLEANSTREAM SOLxSWV 2BR

### 3/8" 4000 PSI CLEANSTREAM BLUE (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400013	HYBD HS 3/8"x25' 4000PSI BLUE CLEANSTREAM SOLxSWV 2BR
489400014	HYBD HS 3/8"x50' 4000PSI BLUE CLEANSTREAM SOLxSWV 2BR
489400015	HYBD HS 3/8"x100' 4000PSI BLUE CLEANSTREAM SOLxSWV 2BR





# PROPULSE COMMERCIAL CLEAN



An economical choice for pressure washer hose. Designed for flow ratings of 2.5 to 5 GPM commercial cleaning applications. Rubber construction throughout, with a single layer of steel wire braid, the hose of choice for manufacturers of commercial duty pressure washers and used by many OEMs in combination with high flow and horsepower.

- › Suitable for commercial pressure cleaning applications
- › Reinforcement: One layer of high tensile braided steel
- › Cover: Choice of smooth cover with printed lay line or wrapped finish with embossed lay line
- › Optional: "Mark-less" cover colors
- › Inner Diameter: 5/16" and 3/8"
- › Working (Maximum): Up to 4000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 250°F
- › Includes jumper hoses
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more
- › **Not for steam**



# COMMERCIAL CLEAN

## 5/16" 3117 PSI RUBBER-WRAPPED BLACK COMMERCIAL (212°F) (1-WIRE BRAID) BURST: 4:1 WORKING PRESSURE

ITEM CODE	DESCRIPTION
989400067	RBR HS BLACK 5/16"x25' 3117PSI M22xM22 2BR
989400072	RBR HS BLACK 5/16"x50' 3117PSI M22xM22 2BR
989400365	RBR HS BLACK 5/16"x50' 3117PSI BL M22xM22 LIVE SWV 2BR

## 3/8" 4000 PSI RUBBER SMOOTH BLACK (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
535100002	RBR HS SM BLACK 3/8"x50' 4000PSI SOLxSWV 2BR
535100005	RBR HS SM BLACK 3/8"x100' 4000PSI SOLxSWV 2BR

\*25' AND 75' AVAILABLE WITH MINIMUM PRODUCTION LEAD TIMES

## 3/8" 4000 PSI RUBBER SMOOTH BLUE (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
535100070	RBR HS SM BLUE 3/8"x25' 4000PSI SOLxSWV 2BR
535100057	RBR HS SM BLUE 3/8"x50' 4000PSI SOLxSWV 2BR
535100071	RBR HS SM BLUE 3/8"x75' 4000PSI SOLxSWV 2BR
535100058	RBR HS SM BLUE 3/8"x100' 4000PSI SOLxSWV 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED GREY COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400007	RBR HS GREY 3/8"x25' 4000PSI SOLxSWV 2BR
989400008	RBR HS GREY 3/8"x50' 4000PSI SOLxSWV 2BR
989400042	RBR HS GREY 3/8"x75' 4000PSI SOLxSWV 2BR
989400043	RBR HS GREY 3/8"x100' 4000PSI SOLxSWV 2BR
989400673	RBR HS GREY 3/8"x150' 4000PSI SOLxSWV 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED BLACK COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400003	RBR HS BLACK 3/8"x25' 4000PSI SOLxSWV 2BR
989400004	RBR HS BLACK 3/8"x50' 4000PSI SOLxSWV 2BR
989400031	RBR HS BLACK 3/8"x75' 4000PSI SOLxSWV 2BR
989400022	RBR HS BLACK 3/8"x100' 4000PSI SOLxSWV 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED BLUE COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400109	RBR HS BLUE 3/8"x25' 4000PSI SOLxSWV 2BR
989400052	RBR HS BLUE 3/8"x50' 4000PSI SOLxSWV 2BR
989400081	RBR HS BLUE 3/8"x100' 4000PSI SOLxSWV 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED YELLOW COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400102	RBR HS YELLOW 3/8"x25' 4000PSI SOLxSWV 2BR
989400099	RBR HS YELLOW 3/8"x50' 4000PSI SOLxSWV 2BR
989400101	RBR HS YELLOW 3/8"x100' 4000PSI SOLxSWV 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED GREY COMMERCIAL WITH QUICK CONNECTS (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400150	RBR HS GREY 3/8"x50' 4000PSI SOLxSWV w/QCs 2BR
989400993	RBR HS GREY 3/8"x100' 4000PSI SOLxSWV w/QCs 2BR

## 3/8" 4000 PSI RUBBER-WRAPPED BLACK COMMERCIAL WITH QUICK CONNECTS (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400075	RBR HS BLACK 3/8"x50' 4000PSI SOLxSWV w/QCs 2BR
989400019	RBR HS BLACK 3/8"x100' 4000PSI SOLxSWV w/QCs 2BR


## 3/8" 4000 PSI RUBBER-WRAPPED GREY JUMPER COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895B5024	RBR HS GREY 3/8"x2' 4000PSI SOLxSWV
9895B5048	RBR HS GREY 3/8"x4' 4000PSI SOLxSWV
9895B5072	RBR HS GREY 3/8"x6' 4000PSI SOLxSWV
9895B5120	RBR HS GREY 3/8"x10' 4000PSI SOLxSWV

## 3/8" 4000 PSI RUBBER-WRAPPED BLACK JUMPER COMMERCIAL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895B3018	RBR HS BLACK 3/8"x18" 4000PSI SOLxSWV
9895B3024	RBR HS BLACK 3/8"x2' 4000PSI SOLxSWV
9895B3036	RBR HS BLACK 3/8"x3' 4000PSI SOLxSWV
9895B3048	RBR HS BLACK 3/8"x4' 4000PSI SOLxSWV
9895B3072	RBR HS BLACK 3/8"x6' 4000PSI SOLxSWV
9895B3120	RBR HS BLACK 3/8"x10' 4000PSI SOLxSWV





# PROPULSE HOT CLEAN



The next level of hot water pressure washer hose. Designed for high flow (up to 8 GPM) heavy duty hot water cleaning applications. Rubber construction throughout, with a double layer of steel wire braid, the hose of choice for manufacturers of hot water pressure washers and used by many OEMs at the upper end of the product range. Generally used in combination with hot water and higher flow and horsepower.

- › Suitable for hot water commercial pressure cleaning applications
- › Reinforcement: Two layers of high tensile braided steel
- › Cover: Wrapped finish with embossed lay line and available in grey "mark-less" cover color
- › Optional: High abrasion resistant Arm-a-Flex™ cover
- › Inner Diameter: 3/8" and 1/2"
- › Working (Maximum): Up to 6000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 250°F
- › Includes jumper hoses
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more
- › **Not for steam**



## HOT CLEAN

### 3/8" 6000 PSI RUBBER-WRAPPED GREY HOT WATER (250°F) (2-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400060	RBR HS GREY 3/8"x50' 6000PSI SOLxSWV 2BR
989400061	RBR HS GREY 3/8"x100' 6000PSI SOLxSWV 2BR

### 3/8" 6000 PSI RUBBER-WRAPPED BLACK HOT WATER (250°F) (2-WIRE BRAID)

ITEM CODE	DESCRIPTION
989400161	RBR HS BLACK 3/8"x25' 6000PSI SOLxSWV 2BR
989400027	RBR HS BLACK 3/8"x50' 6000PSI SOLxSWV 2BR
989400146	RBR HS BLACK 3/8"x75' 6000PSI SOLxSWV 2BR
989400026	RBR HS BLACK 3/8"x100' 6000PSI SOLxSWV 2BR

### 3/8" 4785 PSI RUBBER ARM-A-FLEX BLACK COMMERCIAL (212°F) (2-WIRE BRAID) BURST: 4:1 WORKING PRESSURE

ITEM CODE	DESCRIPTION
989400258	ARM-A-FLEX BLACK 3/8"x50' 4785PSI SOLxSWV 2BR
989400272	ARM-A-FLEX BLACK 3/8"x100' 4785PSI SOLxSWV 2BR

### 1/2" 3987 PSI RUBBER-WRAPPED BLACK COMMERCIAL (212°F) (2-WIRE BRAID) BURST: 4:1 WORKING PRESSURE

ITEM CODE	DESCRIPTION
989400314	RBR HS BLACK 1/2"x50' 3987PSI SOLxSWV 2BR

### 3/8" 6000 PSI RUBBER-WRAPPED GREY JUMPER HOT WATER (250°F) (2-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895B9024	RBR HS GREY 3/8"x2' 6000PSI SOLxSWV
9895B9036	RBR HS GREY 3/8"x3' 6000PSI SOLxSWV
9895B9048	RBR HS GREY 3/8"x4' 6000PSI SOLxSWV
9895B9072	RBR HS GREY 3/8"x6' 6000PSI SOLxSWV
9895B9096	RBR HS GREY 3/8"x8' 6000PSI SOLxSWV
9895B9120	RBR HS GREY 3/8"x10' 6000PSI SOLxSWV

### 3/8" 6000 PSI RUBBER-WRAPPED BLACK JUMPER HOT WATER (250°F) (2-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895B8024	RBR HS BLACK 3/8"x2' 6000PSI SOLxSWV
9895B8036	RBR HS BLACK 3/8"x3' 6000PSI SOLxSWV
9895B8048	RBR HS BLACK 3/8"x4' 6000PSI SOLxSWV
9895B8060	RBR HS BLACK 3/8"x5' 6000PSI SOLxSWV
9895B8072	RBR HS BLACK 3/8"x6' 6000PSI SOLxSWV
9895B8096	RBR HS BLACK 3/8"x8' 6000PSI SOLxSWV
9895B8108	RBR HS BLACK 3/8"x9' 6000PSI SOLxSWV
9895B8120	RBR HS BLACK 3/8"x10' 6000PSI SOLxSWV



# PROPULSE CAR CLEAN

The latest technology from ProPulse provides a real upgrade from the standard carwash self service drop hose. Perfect for self service carwash applications, with both standard rubber and CLEANSTREAM wash bay hoses. Two major maintenance issues carwash owners face with normal rubber hoses are the cleanliness and the wear life of the hose relative to UV and ozone damage. CLEANSTREAM, with an easy to clean, UV and ozone resistant cover, was designed specifically to address these high maintenance and cost issues. CLEANSTREAM hoses are U.S. Patent Pending and possess the unique properties of lightweight, true non-marking, high abrasion resistance and superior flexibility.

- › Suitable for self service carwash applications
- › Reinforcement: One layer of high tensile braided steel
- › Cover: Smooth rubber cover or thermoplastic textured matte finish with printed lay line
- › Inner Diameter: 1/4" and 3/8"
- › Working (Maximum): Up to 4000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 140°F (CLEANSTREAM) and 250°F (Rubber)
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more
- › **Not for hot water or steam**



## 1/4" 3000 PSI RUBBER SMOOTH BLACK WASH BAY (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895PC144	RBR HS SM BLACK 1/4"x12' 3000PSI 3/8"SOLx3/8"SOL 1BR
9895PC180	RBR HS SM BLACK 1/4"x15' 3000PSI 3/8"SOLx3/8"SOL 1BR
9895PC216	RBR HS SM BLACK 1/4"x18' 3000PSI 3/8"SOLx3/8"SOL 1BR

## 1/4" 3000 PSI RUBBER SMOOTH BLUE WASH BAY (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895PH144	RBR HS SM BLUE 1/4"x12' 3000PSI 3/8"SOLx3/8"SOL 1BR
9895PH180	RBR HS SM BLUE 1/4"x15' 3000PSI 3/8"SOLx3/8"SOL 1BR
9895PH216	RBR HS SM BLUE 1/4"x18' 3000PSI 3/8"SOLx3/8"SOL 1BR

## 3/8" 4000 PSI RUBBER SMOOTH BLACK WASH BAY (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895RA144	RBR HS SM BLACK 3/8"x12' 4000PSI SOLxSOL 1BR
9895RA180	RBR HS SM BLACK 3/8"x15' 4000PSI SOLxSOL 1BR
9895RA216	RBR HS SM BLACK 3/8"x18' 4000PSI SOLxSOL 1BR

## 3/8" 4000 PSI RUBBER SMOOTH BLUE WASH BAY (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
9895RJ144	RBR HS SM BLUE 3/8"x12' 4000PSI SOLxSOL 1BR
9895RJ180	RBR HS SM BLUE 3/8"x15' 4000PSI SOLxSOL 1BR
9895RJ216	RBR HS SM BLUE 3/8"x18' 4000PSI SOLxSOL 1BR

## 3/8" 4000 PSI CLEANSTREAM BLACK WASH BAY (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400016	HYBD HS 3/8"x12' 4000PSI BLACK CLEANSTREAM SOLxSOL 1BR
489400017	HYBD HS 3/8"x15' 4000PSI BLACK CLEANSTREAM SOLxSOL 1BR
489400018	HYBD HS 3/8"x18' 4000PSI BLACK CLEANSTREAM SOLxSOL 1BR

## 3/8" 4000 PSI CLEANSTREAM BLUE WASH BAY (140°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
489400019	HYBD HS 3/8"x12' 4000PSI BLUE CLEANSTREAM SOLxSOL 1BR
489400020	HYBD HS 3/8"x15' 4000PSI BLUE CLEANSTREAM SOLxSOL 1BR
489400021	HYBD HS 3/8"x18' 4000PSI BLUE CLEANSTREAM SOLxSOL 1BR





# PROPULSE CARPET CLEAN

Carpet cleaners' preferred choice for hot water solution hoses. Smooth blue and less marking cover with a seamless heat and chemical resistant tube ideal for the commercial carpet cleaning professional.

- › Suitable for commercial carpet cleaning applications
- › Reinforcement: One layer of high tensile braided steel
- › Cover: Smooth blue and less marking cover with printed lay line
- › Inner Diameter: 1/4"
- › Working (Maximum): 3000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 250°F
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more

› **Not for steam**

## 1/4" 3000 PSI RUBBER SMOOTH BLUE CARPET (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
535100059	RBR HS SM BLUE 1/4"x50' 3000PSI SOLxSOL 2BR
535100123	RBR HS SM BLUE 1/4"x75' 3000PSI SOLxSOL 2BR
535100105	RBR HS SM BLUE 1/4"x100' 3000PSI SOLxSOL 2BR
535100118	RBR HS SM BLUE 1/4"x150' 3000PSI SOLxSOL 2BR
535100120	RBR HS SM BLUE 1/4"x200' 3000PSI SOLxSOL 2BR



# PROPULSE CONSUMER CLEAN

These entry level cleaning hoses are best suited for gas and electric cold water pressure washers up to 2.5 GPM. Available in lengths from 25' to 50', these hose assemblies are best suited for residential and light duty cleaning environments.

- › Available in M22xM22 or M22xFBSPP connectors
- › Reinforcement: One layer of polyester braid
- › Cover: Thermoplastic smooth cover with printed lay line
- › Inner Diameter: 1/4"
- › Working (Maximum): Up to 3000 PSI
- › Burst (Minimum) 3:1 working pressure
- › Impulse Life: 100,000+
- › Maximum Temperature: 140°F
- › Volume discounts available in quantities of 10, 20, 30, 40 and 50 or more

› **Not for hot water or steam**

## 1/4" 3000 PSI BLACK CONSUMER (140°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
646200081	PLS HS BLACK 1/4"x25' 3000PSI M22xM22 2BR
646200085	PLS HS BLACK 1/4"x30' 3000PSI M22xM22 2BR
646200098	PLS HS BLACK 1/4"x50' 3000PSI M22xM22 2BR
646200092	PLS HS BLACK 1/4"x25' 3000PSI M22xFBSPP SWV





# PROPULSE JETTER CLEAN

## LATERAL LINE AND DRAIN CLEANER

Ideal for consumer and commercial sewer jetters with operating pressures of 4800 PSI or less and flow rates of 1.5 to 5.0 GPM. These hoses offer optimum flexibility and lightweight construction.

- › Suitable for consumer and commercial applications
- › Reinforcement: One or two layers of polyester braid
- › Cover: Thermoplastic smooth finish with printed lay line
- › Inner Diameter: 1/8", 3/16", 1/4" and 3/8"
- › Working (Maximum): Up to 4800 PSI
- › Burst (Minimum): 2.5:1 working pressure
- › Maximum Temperature: 160°F
- › Volume discounts available in quantities of 10, 20, 30, 40, and 50 or more



### 1/8" 4800 PSI BLACK JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200047	SWR HS BLACK 1/8"x25' 4800PSI SOLxSOL w/1/4" BUSHING
686200007	SWR HS BLACK 1/8"x50' 4800PSI SOLxSOL w/1/4" BUSHING
686200017	SWR HS BLACK 1/8"x75' SOLxSOL w/1/4" BUSHING
686200051	SWR HS BLACK 1/8"x100' 4800PSI SOLxSOL w/1/4" BUSHING
686200053	SWR HS BLACK 1/8"x200' 4800PSI SOLxSOL w/1/4" BUSHING

### 3/16" 4800 PSI BLACK JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200006	SWR HS BLACK 3/16"x50' 4800PSI 1/4"SOLx1/8"SOL
686200005	SWR HS BLACK 3/16"x100' 4800PSI 1/4"SOLx1/8"SOL


### 1/4" 4400 PSI BLACK JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200032	SWR HS BLACK 1/4"x50' 4400PSI SOLxSWV
686200012	SWR HS BLACK 1/4"x100' 4400PSI SOLxSWV
686200010	SWR HS BLACK 1/4"x150' 4400PSI SOLxSWV
686200020	SWR HS BLACK 1/4"x200' 4400PSI SOLxSWV
686200050	SWR HS BLACK 1/4"x300' 4400PSI SOLxSWV

### 3/8" 4000 PSI BLACK JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200033	SWR HS BLACK 3/8"x50' 4000PSI SOLxSWV
686200021	SWR HS BLACK 3/8"x100' 4000PSI SOLxSWV
686200034	SWR HS BLACK 3/8"x150' 4000PSI SOLxSWV
686200025	SWR HS BLACK 3/8"x200' 4000PSI SOLxSOL
686200011	SWR HS BLACK 3/8"x200' 4000PSI SOLxSWV
686200035	SWR HS BLACK 3/8"x300' 4000PSI SOLxSWV





# PROPULSE JETTER CLEAN MAINLINE

Commercial and municipal cleaning hoses with operating pressures of 2500, 3000 and 4000 PSI designed for truck or trailer mount sewer jetter applications.

- › Suitable replacements for factory installed sewer jetter cleaning hoses
- › Reinforcement: Two layers of polyester braid
- › Cover: Thermoplastic smooth finish with printed lay line
- › Inner Diameter: 1/2", 3/4" and 1"
- › Working (Maximum): Up to 4000 PSI
- › Burst (Minimum): 2.5:1 working pressure
- › Maximum Temperature: 160°F
- › Leader hoses available in 15' and 20' two wire reinforced rubber
- › Volume discounts available in quantities of 4, 7, 10, 13 and 16 or more

**STANDARD 24-HOUR SHIPPING COMMITMENT NOT GUARANTEED FOR 3/4" AND 1" SEWER JETTER ASSEMBLIES; PLEASE CONTACT YOUR SERVICE TEAM FOR AVAILABILITY.**



## 1/2" 4000 PSI GREEN JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200100	SWR HS GREEN 1/2"x50' 4000PSI SOLxSWV
686200094	SWR HS GREEN 1/2"x100' 4000PSI SOLxSWV
686200062	SWR HS GREEN 1/2"x200' 4000PSI SOLxSWV
686200058	SWR HS GREEN 1/2"x300' 4000PSI SOLxSWV
686200120	SWR HS GREEN 1/2"x400' 4000PSI SOLxSWV
686200090	SWR HS GREEN 1/2"x500' 4000PSI SOLxSWV

## 3/4" 2500 PSI ORANGE JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200160	SWR HS ORANGE 3/4"x400' 2500PSI SOLxSOL
686200161	SWR HS ORANGE 3/4"x500' 2500PSI SOLxSOL
686200162	SWR HS ORANGE 3/4"x600' 2500PSI SOLxSOL
686200184	SWR HS ORANGE 3/4"x700' 2500PSI SOLxSOL

## 1" 2500 PSI ORANGE JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200163	SWR HS ORANGE 1"x400' 2500PSI SOLxSOL
686200164	SWR HS ORANGE 1"x500' 2500PSI SOLxSOL
686200165	SWR HS ORANGE 1"x600' 2500PSI SOLxSOL
686200185	SWR HS ORANGE 1"x700' 2500PSI SOLxSOL
686200228	SWR HS ORNAGE 1"x800' 2500PSI SOLxSOL

## 3/4" 3000 PSI BLUE JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200134	SWR HS BLUE 3/4"x500' 3000PSI SOLxSOL
686200135	SWR HS BLUE 3/4"x600' 3000PSI SOLxSOL

## 1" 3000 PSI BLUE JETTER HOSES (160°F) (TEXTILE BRAID)

ITEM CODE	DESCRIPTION
686200136	SWR HS BLUE 1"x500' 3000PSI SOLxSOL
686200137	SWR HS BLUE 1"x600' 3000PSI SOLxSOL

## 3/4" 3117 PSI RUBBER-WRAPPED BLACK LEADER HOSE (212°F) (2-WIRE BRAID) BURST: 4:1 WORKING PRESSURE

ITEM CODE	DESCRIPTION
989400987	RBR HS BLACK 3/4"x15' 3117PSI SOLxFSWV
989400988	RBR HS BLACK 3/4"x20' 3117PSI SOLxFSWV

## 1" 3045 PSI RUBBER-WRAPPED BLACK LEADER HOSE (212°F) (2-WIRE BRAID) BURST: 4:1 WORKING PRESSURE

ITEM CODE	DESCRIPTION
989400990	RBR HS BLACK 1"x15' 3045PSI SOLxFSWV
989400991	RBR HS BLACK 1"x20' 3045PSI SOLxFSWV

# PROPULSE BULK HOSE REELS

These industry standard bulk smooth and wrapped rubber pressure washer hoses designed for up to 5 GPM heavy duty cleaning applications are available in hose reel lengths of 250' and 500'. Rubber construction throughout, with one or two layers of wire braid, these have been the hose of choice for manufacturers of commercial duty pressure washers. Reels are an ideal option for customizing hose assemblies for the unique needs of your customer.

- › Suitable for cold and hot water commercial pressure cleaning applications
- › Reinforcement: One or two layers of high tensile braided steel
- › Cover: Choice of smooth cover with printed lay line or wrapped finish with embossed lay line
- › Optional: "Mark-less" cover colors
- › Inner Diameter: 1/4" and 3/8"
- › Working (Maximum): 4000 and 6000 PSI
- › Burst (Minimum): 3:1 working pressure
- › Impulse Life: 200,000+
- › Maximum Temperature: 250°F
- › 250' reels contain up to two splices with a minimum length of 100'
- › 500' reels contain up to three splices with a minimum length of 100'
- › Volume discounts available in quantities of 4, 7, 10, 13 and 16 or more

**STANDARD 24-HOUR SHIPPING COMMITMENT NOT GUARANTEED FOR BULK HOSE REELS; PLEASE CONTACT YOUR SERVICE TEAM FOR AVAILABILITY.**



## 1/4" 3000 PSI BULK SMOOTH RUBBER CLEANING HOSE REEL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
SHPW-04-250RL	250' BULK RBR HS SM BLACK 1WIRE DN6 3000PSI
SHPW-04-500RL	500' BULK RBR HS SM BLACK 1WIRE DN6 3000PSI
SHPW-04BL-250RL	250' BULK RBR HS SM BLUE 1WIRE DN6 3000PSI
SHPW-04BL-500RL	500' BULK RBR HS SM BLUE 1WIRE DN6 3000PSI

## 3/8" 4000 PSI BULK SMOOTH RUBBER CLEANING HOSE REEL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
SHPW-06-250RL	250' BULK RBR HS SM BLACK 1WIRE DN10 4000PSI
SHPW-06-500RL	500' BULK RBR HS SM BLACK 1WIRE DN10 4000PSI
SHPW-06BL-250RL	250' BULK RBR HS SM BLUE 1WIRE DN10 4000PSI
SHPW-06BL-500RL	500' BULK RBR HS SM BLUE 1WIRE DN10 4000PSI

## 3/8" 4000 PSI BULK-WRAPPED RUBBER CLEANING HOSE REEL (250°F) (1-WIRE BRAID)

ITEM CODE	DESCRIPTION
HPW1-06-250RL	250' BULK RBR HS BLACK 1WIRE DN10 4000PSI
HPW1-06-500RL	500' BULK RBR HS BLACK 1WIRE DN10 4000PSI
HPW1-06GR-250RL	250' BULK RBR HS GREY 1WIRE DN10 4000PSI
HPW1-06GR-500RL	500' BULK RBR HS GREY 1WIRE DN10 4000PSI
HPW1-06BL-250RL	250' BULK RBR HS BLUE 1WIRE DN10 4000PSI
HPW1-06BL-500RL	500' BULK RBR HS BLUE 1WIRE DN10 4000PSI
HPW1-06YL-250RL	250' BULK RBR HS YELLOW 1WIRE DN10 4000PSI
HPW1-06YL-500RL	500' BULK RBR HS YELLOW 1WIRE DN10 4000PSI

## 3/8" 6000 PSI BULK-WRAPPED RUBBER CLEANING HOSE REEL (250°F) (2-WIRE BRAID)

ITEM CODE	DESCRIPTION
HPW2-06-250RL	250' BULK RBR HS BLACK 2WIRE DN10 6000PSI
HPW2-06-500RL	500' BULK RBR HS BLACK 2WIRE DN10 6000PSI
HPW2-06GR-250RL	250' BULK RBR HS GREY 2WIRE DN10 6000PSI
HPW2-06GR-500RL	500' BULK RBR HS GREY 2WIRE DN10 6000PSI



# PROPULSE

## QUICK CONNECT SOCKETS AND PLUGS

For quick changeover and installation of common high pressure cleaning assemblies.

- › FST straight thru style (no check valve in either socket or plug)
- › Available in brass, zinc plated steel and stainless steel
- › Available in 1/4", 3/8" and 1/2" in both male and female configurations
- › Buna-N O-ring has excellent ozone, chemical and aging resistance
- › Viton® O-ring standard on items 14-0389 and 14-0376
- › Viton® replacement O-rings available upon request and sold separately
- › Minimum/Maximum Temperature Operating Range: -40°F / 250°F
- › Optional Viton® O-ring Minimum/Maximum Temperature Operating Range: -15°F / 400°F
- › Volume discounts available in quantities of 25, 50, 100, 200 and 300 or more

**STANDARD 24-HOUR SHIPPING COMMITMENT NOT GUARANTEED;  
PLEASE CONTACT YOUR SERVICE TEAM FOR AVAILABILITY.**



### 1/4" QUICK CONNECTS

ITEM CODE	DESCRIPTION
14-0396	QC 1/4" FNPT BRASS SOCKET
14-0414	QC 1/4" FNPT S.S. SOCKET
14-0411	QC 1/4" FNPT BRASS PLUG
14-0399	QC 1/4" FNPT ZINC STEEL PLUG
14-0403	QC 1/4" FNPT S.S. PLUG
14-0397	QC 1/4" MNPT BRASS SOCKET
14-0406	QC 1/4" MNPT BRASS PLUG
14-0400	QC 1/4" MNPT ZINC STEEL PLUG
14-0402	QC 1/4" MNPT S.S. PLUG
10-0018	1/4" VITON® O-RING

### 3/8" QUICK CONNECTS

ITEM CODE	DESCRIPTION
14-0389	QC 3/8" FNPT BRASS SOCKET
14-0376	QC 3/8" FNPT S.S. SOCKET
14-0412	QC 3/8" FNPT BRASS PLUG
14-0390	QC 3/8" FNPT ZINC STEEL PLUG
14-0377	QC 3/8" FNPT S.S. PLUG
14-0398	QC 3/8" MNPT BRASS SOCKET
14-0407	QC 3/8" MNPT BRASS PLUG
14-0401	QC 3/8" MNPT ZINC STEEL PLUG
14-0391	QC 3/8" MNPT S.S. PLUG
10-0019	3/8" VITON® O-RING

### 1/2" QUICK CONNECTS

ITEM CODE	DESCRIPTION
14-0409	QC 1/2" FNPT BRASS SOCKET
14-0413	QC 1/2" FNPT BRASS PLUG
14-0410	QC 1/2" FNPT STEEL PLUG
14-0408	QC 1/2" MNPT BRASS PLUG
14-0404	QC 1/2" MNPT BRASS SOCKET
14-0405	QC 1/2" MNPT STEEL PLUG
10-0020	1/2" VITON® O-RING

# PROPULSE

# ORDERING INFORMATION

## PROPULSE NOW DISCOUNT PROGRAM:

---

Discounts are available based on annual purchase commitments to ProPulse or volume purchase quantities. Please contact the ProPulse service teams for the annual purchase requirements and details on the discount program.

## IN-STOCK PROPULSE ORDERS:

---

- › All orders ship within 24 hours
- › Orders ship F.O.B. Peosta, Iowa
- › \$100 minimum purchase order requirement
  - › \$20 convenience fee applies to all orders under \$100
- › Drop ship orders add an additional \$10 per shipping address
- › Open credit terms available: VISA®, MASTERCARD® and DISCOVER® accepted
  - › 3% convenience fee applies to all credit card transactions
- › ProPulse has the right to substitute a product of equal or greater performance at any time
- › Pricing and specifications are subject to change at any time



## NON-STOCK PROPULSE ORDERS:

---

- › Minimum order quantity of 10 assemblies equaling a minimum of \$250 per item
- › Requires completion of "STAMPED Worksheet"
- › Upon completion of request form, quote and lead time will be provided within 48 hours

**CREDIT RETURNS:** We accept credit returns of in-stock ProPulse items up to 90 days after purchase with a 15% restocking fee. Please contact your service team for "Return Materials Authorization" (RMA). Return shipping costs must be prepaid by you and include a copy of the RMA. When returning item(s), credit (less the original shipping and restocking fees) will be issued upon return and evaluation of original condition. Due to the custom nature of non-stock items, credit returns are not accepted. For warranty returns, please refer to our limited warranty policy.

## ORDER THESE INNOVATIVE PRODUCTS TODAY.





# PROPULSE STAMPED WORKSHEET

At ProPulse, we know that some projects require a custom hose solution. To help us quote and build the perfect hose assembly for your application, please complete this worksheet.

Experienced sales team members are just a phone call away, and knowledgeable field representatives are available when a site visit may be necessary.

› NAME:

› COMPANY:

› PHONE #:

› E-MAIL:

› DATE:

## S – SIZE

› What size is the hose?

› Inside Diameter (I.D.):

› Outside Diameter (O.D.):

› Coupled length (OAL):

## T – TEMPERATURE

› Temperature of product being transferred:

Min:

Max:

› Temperature of the environment:

Min:

Max:

## A – APPLICATION

› How is the hose being used: ☐ Suction ☐ Discharge ☐ Pressure

## M – MATERIAL

› What material is going through the hose? (Please include product that is normally transferred as well as any cleaning fluids.)

## P – PRESSURE

› What is the maximum pressure (PSI) or suction (in/HG)? SAE or DIN rating? Bend Radius?

## E – ENDS

› What fittings do you want on each end or do you want it open ended? (Type: elbow / long drop / male / female / swivel / plating)

## D – DELIVERY

› When do you want the hose?

› Estimated annual usage (EAU) and typical purchase quantities:

› Testing required?

☐ Yes

☐ No

› Certification required?

☐ Yes

☐ No

## OTHER NOTES

› Any issues with your current hose? Or objectives you are trying to address (i.e. flexibility, abrasion, environment, routing)?



REQUEST A QUOTE TODAY.

**PROPULSE**  
A SCHIEFFER CO.

PHONE 563.583.4758

TOLL-FREE 877.384.4673

FAX 800.303.4673

EMAIL [info@powermovingforward.com](mailto:info@powermovingforward.com)

[www.PowerMovingForward.com](http://www.PowerMovingForward.com)

# PROPULSE LIMITED WARRANTY

Subject to the limitations stated herein, Schieffer Co. International, L.C., dba ProPulse (Seller) warrants that the products manufactured by Seller identified below shall be free from material defects in materials and workmanship and shall perform the services for which they are intended when properly installed, under normal use, and under ordinary conditions, for:

**HYDRAULIC HOSE:** A period of 365 days from the date of shipment of the product to BUYER.

**HIGH PRESSURE CLEANING HOSE:** A period of 180 days from the shipment of the product to the BUYER.

Buyer must notify Seller in writing of a potentially defective product as soon as possible, which notice must provide the appropriate marked date codes, part numbers of the product and a description of the potential defect. Upon receipt of such notice, Seller shall, at its option and at its expense, examine such product at Seller's factory or such other location as Seller shall determine. Should Seller agree to a return of the product, Buyer shall follow in every respect the packaging and transportation instructions provided by Seller. In no case shall a product be returned without first obtaining the permission of Seller. If a product is proven to the satisfaction of Seller to be defective, then Seller shall, at its option and at its expense, repair or replace such product or reimburse Buyer for the price paid by Buyer for such product, and credit will be issued to Buyer to offset the expense of the return shipment to Seller for shipments within the continental United States. The cost of shipping to Buyer a repaired or replaced product shall be paid by Seller on the same shipping terms as the original shipment of such product to Buyer. Except as stated herein, Buyer shall assume all responsibility and expense for any dismantling, removal, reinstallation, and shipping in connection with this Limited Warranty, and no claims will be allowed for labor, shipping, materials, incidental, consequential, or other costs incident to the repair, replacement, or return of a product.

THIS LIMITED WARRANTY IS THE ONLY WARRANTY PROVIDED BY SELLER AND IS MADE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND THOSE ARISING BY OPERATION OF LAW, TRADE USAGE, OR COURSE OF DEALING.

NOTWITHSTANDING THE FOREGOING, THERE ARE NO WARRANTIES WHATSOEVER ON PRODUCTS BUILT OR ACQUIRED WHOLLY OR PARTIALLY TO BUYER'S DESIGNS OR SPECIFICATIONS.

SELLER'S LIABILITY IS LIMITED TO REPAIR, REPLACEMENT, OR REIMBURSEMENT AS PROVIDED ABOVE, AND IN NO EVENT SHALL SELLER'S LIABILITY EXCEED THE PURCHASE PRICE OF THE PRODUCT(S)

INVOLVED. THIS LIMITED WARRANTY PROVIDES THE EXCLUSIVE REMEDY AGAINST SELLER FOR CLAIMS RELATING TO PRODUCTS, WHETHER IN CONTRACT, IN TORT (INCLUDING NEGLIGENCE), OR UNDER ANY OTHER LEGAL THEORY, AND WHETHER ARISING OUT OF WARRANTIES, REPRESENTATIONS, INSTRUCTIONS, OR DEFECTS FROM ANY CAUSE. IN NO EVENT SHALL SELLER BE LIABLE FOR OR OBLIGATED TO PAY ANY CONSEQUENTIAL, INCIDENTAL, SPECIAL, INDIRECT, OR PUNITIVE DAMAGES OF ANY KIND, INCLUDING, BUT NOT LIMITED TO LOST PROFITS.

THIS LIMITED WARRANTY EXTENDS ONLY TO BUYERS WHO PURCHASE SELLER'S PRODUCT(S) DIRECTLY FROM SELLER ("ORIGINAL PURCHASERS"), INCLUDING MANUFACTURERS, RETAILERS, DEALERS, DISTRIBUTORS AND WHOLESALERS. THIS LIMITED WARRANTY IS NOT ASSIGNABLE OR OTHERWISE TRANSFERRABLE BY THE ORIGINAL PURCHASER TO ANY OTHER PARTY. SELLER EXTENDS NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, TO "CONSUMERS," AS THAT TERM IS DEFINED IN THE MAGNUSON-MOSS WARRANTY ACT (15 U.S.C. SECTIONS 2301 ET SEQ.) AND THE REGULATIONS PROMULGATED THEREUNDER. IN NO EVENT SHALL THE DURATION OF ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE BE LONGER THAN THE PERIOD PRESCRIBED HEREIN.

This Limited Warranty shall not apply to product failure or defect: caused by external or internal abrasion, kinking, twisting, cutting, pulling, impact, use for the transfer or spray of flammable materials (including solvents, petroleum, and gases of any kind), use with fluids which exceed the product's labeled pressure or temperature limits, storm, fire, wind, accident, or similar casualty; where the product has been modified without the prior written authority of Seller; caused by installation or use of the product contrary to any instructions or specifications provided by Seller; caused by the improper installation, use, application, maintenance, repair, transportation, handling, or storage of the product; caused by the fault or negligence of anyone other than Seller or any other act or event beyond the control of Seller. Seller makes no warranties as to any products or product parts or components that are not manufactured by Seller, and such items may be warranted only to the extent of the original manufacturer's warranty, if any. The limitations of liability contained in this Limited Warranty shall be effective without regard to Seller's performance or failure or delay of performance under any other term or condition of any trade customs, warranty, or other agreement. No employee, representative, or agent of Seller, nor any other person, has authority to assume or incur on behalf of Seller any liability, obligation, or responsibility in place of or in addition to this Limited Warranty.

THE  
**PROPULSE**<sup>®</sup>  
— DIFFERENCE —



We have the right balance of experience and flexibility to make incredible improvements to a wide range of markets—innovating current standards is our strong suit. So far we've gone above and beyond with the following products, and it's a trend we plan to continue:

- › CLEANSTREAM™
- › UberFlex™
- › Arm-a-Flex™
- › And more in the works



**PROPULSE**<sup>®</sup>  
A SCHIEFFER CO.





8545 Kapp Drive  
P.O. Box 13  
Peosta, IA 52068-0013

**PHONE** 563.583.4758

**TOLL-FREE** 877.384.4673

**FAX** 800.303.4673

**EMAIL** [info@powermovingforward.com](mailto:info@powermovingforward.com)

**[www.PowerMovingForward.com](http://www.PowerMovingForward.com)**