
HYDRAULIC FITTINGS



SMART PART NUMBERING

SMART part number example with part description:



= Female, ORFS, Straight, Hydraulic, Long "Style B", 3/8" x 3/8"

| | 1 – PREFIX |
|----|------------------------|
| S | Schieffer |
| | 2 – FITTING GENDER |
| I | Male |
| 2 | Female |
| 3 | Nipple |
| 4 | Banjo Fitting |
| 5 | SAE Flange |
| | 3 — FITTING SERIES |
| 22 | Metric Banjo |
| 26 | Metric DKOL |
| 27 | Metric DKOS |
| 33 | Pressure Washer Nipple |
| 38 | NPSM |
| 42 | BSP Banjo |
| 44 | BSP O-Ring Flat Seal |
| 48 | BSP 60° Cone |
| 52 | BSPT |
| 64 | ORFS |
| 78 | NPT |
| 82 | Standard ORB |
| 89 | JIC |
| 95 | Code 61 Flange |
| 98 | Code 62 Flange |
| | 4 — FITTING TYPE |
| I | Straight |
| 2 | 22.5° |
| 4 | 45° |
| 9 | 90° |
| | 5 — APPLICATION TYPE |
| I | Hydraulic |
| 3 | Pressure Washer Only |
| | |

| | 6 - SPECIALTIES (OPTIONAL) |
|---------|----------------------------|
| W | Swivel |
| S | Short |
| M | Medium |
| L | Long |
| D | Double Hex |
| ВН | Bulk Head |
| | 7 – THREAD SIZE |
| -2 | 1/8" |
| -3 | 3/16" |
| -4 | 1/4" |
| -5 | 5/16 |
| -6 | 3/8" |
| -8 | 1/2" |
| -IO | 5/8" |
| -12 | 3/4" |
| -14 | 7/8" |
| -16 | 1" |
| | 8 – HOSE SIZE |
| -2 | 1/8" |
| -3 | 3/16" |
| -4 | 1/4" |
| -5 | 5/16 |
| -6 | 3/8" |
| -8 | 1/2" |
| -IO | 5/8" |
| -12 | 3/4" |
| -14 | 7/8" |
| -16 | 1" |
| | 9 – PLATING/ MATERIAL |
| (BLANK) | Standard |
| ZN | Zinc Nickel* |
| 55 | Stainless Steel* |
| | |


^{*} Consult with sales representative for availability.

HYDRAULIC FITTINGS (SERIES INDEX)

| | PROPULSE FITTINGS SERIES | |
|---------------|--|------|
| HOSE SERIES | DESCRIPTION | PAGE |
| 226II SERIES | Metric Female 24° Cone O-Ring DKOL Straight > > DIN 20066/3865 | 35 |
| 2264I SERIES | Metric Female 24° Cone O-Ring DKOL 45° Elbow > DIN 20066/3865 | 36 |
| 2269I SERIES | Metric Female 24° Cone O-Ring DKOL 90° Elbow > DIN 20066/3865 | 37 |
| 12611 SERIES | Metric Male 24° Cone Seat DKOL Straight > DIN 20066/3861 | 38 |
| 227II SERIES | Metric Female 24° Cone O-Ring DKOS Straight > DIN 20066/3865 | 39 |
| 2274I SERIES | Metric Female 24° Cone O-Ring DKOS 45° Elbow > DIN 20066/3865 | 40 |
| 2279I SERIES | Metric Female 24° Cone O-Ring DKOS 90° Elbow > DIN 20066/3865 | 41 |
| 12711 SERIES | Metric Male 24° Cone Seat DKOS Straight > DIN 20066/3861 | 42 |
| 722II SERIES | Metric Banjo > DIN 7642 | 43 |
| 264IIS SERIES | ORFS Female Short Straight > SAE J1453/J516 | 44 |
| 264IIL SERIES | ORFS Female Long Straight > SAE J1453/J516 | 45 |
| 2644I SERIES | ORFS Female 45° Elbow > SAE J1453/J516 | 46 |
| 2649I SERIES | ORFS Female 90° Elbow > SAE J1453/J516 | 47 |
| 2649IM SERIES | ORFS Female 90° Elbow Medium Drop > SAE J1453/J516 | 48 |
| 2649IL SERIES | ORFS Female 90° Elbow Long Drop > SAE J1453/J516 | 49 |
| 16411 SERIES | ORFS Male Straight > SAE J1453/J516 | 50 |
| 289IID SERIES | JIC Female 37° Cone Double Hex Straight > SAE J514/J516 | 51 |
| 2894I SERIES | JIC Female 37° Cone 45° Elbow > SAE J514/J516 | 52 |
| 2899I SERIES | JIC Female 37° Cone 90° Elbow > SAE J514/J516 | 53 |
| 2899IM SERIES | JIC Female 37° Cone 90° Elbow Medium Drop > SAE J514/J516 | 54 |
| 2899IL SERIES | JIC Female 37° Cone 90° Elbow Long Drop > SAE J514/J516 | 55 |
| 18911 SERIES | JIC Male 37° Cone Straight > SAE J514/J516 | 56 |
| 238II SERIES | NPSM Female 30° Cone Straight | 57 |
| 17811 SERIES | NPTF Male 30° Cone Straight > SAE J516 | 58 |
| 17811W SERIES | NPTF Swivel Male 30° Cone Straight > SAE J516 | 59 |
| 278II SERIES | NPT Female Solid Straight | 60 |
| 248II SERIES | BSP Female 60° Cone Straight | 61 |
| 2484I SERIES | BSP Female 60° Cone 45° Elbow | 62 |
| 2489I SERIES | BSP Female 60° Cone 90° Elbow | 63 |
| 14811 SERIES | BSP Male 60° Cone Straight | 64 |
| 144II SERIES | BSPP Male O-Ring Flat Seal Straight | 65 |
| 244II SERIES | BSP Female Flat Seal Straight | 66 |
| I52II SERIES | BSPT Male Straight | 67 |
| 742II SERIES | BSP Banjo | 68 |
| 895II SERIES | SAE Code 61 3000PSI Flange Straight > SAE J516/J518 | 69 |

HYDRAULIC FITTINGS (SERIES INDEX)

| HOSE SERIES | DESCRIPTION | PAGE |
|---------------|--|------|
| 8954I SERIES | SAE Code 61 3000PSI Flange 45° Elbow > SAE J516/J518 | 70 |
| 8959I SERIES | SAE Code 61 3000PSI Flange 90° Elbow > SAE J516/J518 | 71 |
| 898II SERIES | SAE Code 62 6000PSI Flange Straight > SAE J516/J518 | 72 |
| 8984I SERIES | SAE Code 62 6000PSI Flange 45° Elbow > SAE J516/J518 | 73 |
| 8989I SERIES | SAE Code 62 6000PSI Flange 90° Elbow > SAE J516/J518 | 74 |
| 18211 SERIES | Standard ORB Male Solid > SAE J514/J516 | 75 |
| 18211W SERIES | Standard ORB Male Swivel > SAE J514/J516 | 76 |




METRIC FEMALE 24° CONE O-RING DKOL STRAIGHT DIN 20066/3865


| 226II SERIES | THREAD | HOS | E BORE | DIMENS | SIONS (MM) |
|---------------------------|-----------|-----|--------|--------|------------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | |
| S22611-10-02 | M10 x 1.0 | 4 | 2 | 12 | |
| S22611-12-02 | M12 x 1.5 | 4 | 2 | 14 | |
| S22611-12-04 | M12 x 1.5 | 6 | 4 | 17 | |
| S22611-14-04 | M14 x 1.5 | 6 | 4 | 17 | |
| S22611-16-04 | M16 x 1.5 | 6 | 4 | 22 | |
| S22611-18-04 | M18 x 1.5 | 6 | 4 | 22 | |
| S22611-14-05 | M14 x 1.5 | 8 | 5 | 17 | |
| S22611-16-05 | M16 x 1.5 | 8 | 5 | 19 | |
| S22611-18-05 | M18 x 1.5 | 8 | 5 | 22 | |
| S22611-22-05 | M22 x 1.5 | 8 | 5 | 27 | |
| S22611-14-06 | M14 x 1.5 | 10 | 6 | 19 | |
| S22611-16-06 | M16 x 1.5 | 10 | 6 | 22 | |
| S22611-18-06 | M18 x 1.5 | 10 | 6 | 22 | |
| S22611-22-06 | M22 x 1.5 | 10 | 6 | 27 | |
| S22611-18-08 | M18 x 1.5 | 12 | 8 | 24 | |
| S22611-22-08 | M22 x 1.5 | 12 | 8 | 27 | |
| S22611-22-10 | M22 x 1.5 | 16 | 10 | 27 | |
| S22611-26-10 | M26 x 1.5 | 16 | 10 | 32 | |
| S22611-30-10 | M30 x 2 | 16 | 10 | 36 | |
| S22611-26-12 | M26 x 1.5 | 19 | 12 | 32 | |
| S22611-30-12 | M30 x 2 | 19 | 12 | 36 | |
| S22611-36-12 | M36 x 2 | 19 | 12 | 41 | |
| S22611-30-16 | M30 x 2 | 25 | 16 | 36 | |
| S22611-36-16 | M36 x 2 | 25 | 16 | 41 | |
| S22611-45-16 | M45 x 2 | 25 | 16 | 50 | |
| S22611-36-20 | M36 x 2 | 32 | 20 | 41 | |
| S22611-45-20 | M45 x 2 | 32 | 20 | 50 | |
| S22611-52-20 | M52 x 2 | 32 | 20 | 60 | |
| S22611-52-24 | M52 x 2 | 38 | 24 | 60 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

METRIC FEMALE 24° CONE O-RING DKOL 45° ELBOW DIN 20066/3865







| 2264I SERIES | THREAD | HOSE | HOSE BORE DIMENSIONS (MM) | | ONS (MM) |
|---------------------------|-----------|------|---------------------------|-----|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | Н |
| S22641-14-04 | M14 x 1.5 | 6 | 4 | 19 | 16 |
| S22641-16-05 | M16 x 1.5 | 8 | 5 | 19 | 17 |
| S22641-18-05 | M18 x 1.5 | 8 | 5 | 22 | 18.5 |
| S22641-22-05 | M22 x 1.5 | 8 | 5 | 27 | 19.5 |
| S22641-16-06 | M16 x 1.5 | 10 | 6 | 19 | 17 |
| S22641-18-06 | M18 x 1.5 | 10 | 6 | 22 | 18.5 |
| S22641-22-06 | M22 x 1.5 | 10 | 6 | 27 | 19.5 |
| S22641-22-08 | M22 x 1.5 | 12 | 8 | 27 | 19.5 |
| S22641-26-08 | M26 x 1.5 | 12 | 8 | 32 | 23.5 |
| S22641-26-10 | M26 x 1.5 | 16 | 10 | 32 | 23.5 |
| S22641-30-10 | M30 x 2 | 16 | 10 | 36 | 25.5 |
| S22641-26-12 | M26 x 1.5 | 19 | 12 | 32 | 23.5 |
| S22641-30-12 | M30 x 2 | 19 | 12 | 36 | 25.5 |
| S22641-36-12 | M36 x 2 | 19 | 12 | 41 | 32 |
| S22641-36-16 | M36 x 2 | 25 | 16 | 41 | 32 |
| S22641-45-20 | M45 x 2 | 32 | 20 | 50 | 38 |
| S22641-52-20 | M52 x 2 | 32 | 20 | 60 | 44.5 |
| S22641-52-24 | M52 x 2 | 38 | 24 | 60 | 44.5 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



METRIC FEMALE 24° CONE O-RING DKOL 90° ELBOW DIN 20066/3865




| 2269I SERIES | THREAD | HOSE | BORE | DRE DIMENSION | |
|---------------------------|-----------|------|------|---------------|------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н |
| S22691-12-04 | M12 x 1.5 | 6 | 4 | 14 | 30 |
| S22691-14-04 | M14 x 1.5 | 6 | 4 | 17 | 30.5 |
| S22691-16-04 | M16 x 1.5 | 6 | 4 | 22 | 33 |
| S22691-14-05 | M14 x 1.5 | 8 | 5 | 17 | 30.5 |
| S22691-16-05 | M16 x 1.5 | 8 | 5 | 19 | 33 |
| S22691-18-05 | M18 x 1.5 | 8 | 5 | 22 | 36 |
| S22691-16-06 | M16 x 1.5 | 10 | 6 | 19 | 36 |
| S22691-18-06 | M18 x 1.5 | 10 | 6 | 22 | 36 |
| S22691-22-06 | M22 x 1.5 | 10 | 6 | 27 | 40.5 |
| S22691-22-08 | M22 x 1.5 | 12 | 8 | 27 | 40.5 |
| S22691-26-08 | M26 x 1.5 | 12 | 8 | 32 | 51.5 |
| S22691-26-10 | M26 x 1.5 | 16 | 10 | 32 | 51.5 |
| S22691-30-10 | M30 x 2 | 16 | 10 | 36 | 56 |
| S22691-26-12 | M26 x 1.5 | 19 | 12 | 32 | 51.5 |
| S22691-30-12 | M30 x 2 | 19 | 12 | 36 | 56 |
| S22691-36-12 | M36 x 2 | 19 | 12 | 41 | 68.5 |
| S22691-30-16 | M30 x 2 | 25 | 16 | 36 | 56 |
| S22691-36-16 | M36 x 2 | 25 | 16 | 41 | 68.5 |
| S22691-45-16 | M45 x 2 | 25 | 16 | 50 | 78.5 |
| S22691-36-20 | M36 x 2 | 32 | 20 | 41 | 68.5 |
| S22691-45-20 | M45 x 2 | 32 | 20 | 50 | 78.5 |
| S22691-52-20 | M52 x 2 | 32 | 20 | 60 | 95 |
| S22691-52-24 | M52 x 2 | 38 | 24 | 60 | 95 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


METRIC MALE 24° CONE SEAT DKOL STRAIGHT DIN 20066/3861



| 12611 SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|-----------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | |
| S12611-12-04 | M12 x 1.5 | 6 | 4 | 14 | |
| S12611-14-04 | M14 x 1.5 | 6 | 4 | 17 | |
| S12611-16-04 | M16 x 1.5 | 6 | 4 | 17 | |
| S12611-14-05 | M14 x 1.5 | 8 | 5 | 17 | |
| S12611-16-05 | M16 x 1.5 | 8 | 5 | 17 | |
| S12611-18-05 | M18 x 1.5 | 8 | 5 | 19 | |
| S12611-16-06 | M16 x 1.5 | 10 | 6 | 17 | |
| S12611-18-06 | M18 x 1.5 | 10 | 6 | 19 | |
| S12611-22-06 | M22 x 1.5 | 10 | 6 | 24 | |
| S12611-22-08 | M22 x 1.5 | 12 | 8 | 24 | |
| S12611-26-08 | M26 x 1.5 | 12 | 8 | 27 | |
| S12611-22-10 | M22 x 1.5 | 16 | 10 | 22 | |
| S12611-26-10 | M26 x 1.5 | 16 | 10 | 27 | |
| S12611-30-10 | M30 x 2 | 16 | 10 | 32 | |
| S12611-30-12 | M30 x 2 | 19 | 12 | 32 | |
| S12611-36-16 | M36 x 2 | 25 | 16 | 41 | |
| S12611-45-20 | M45 x 2 | 32 | 20 | 46 | |
| S12611-52-24 | M52 x 2 | 38 | 24 | 55 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




METRIC FEMALE 24° CONE O-RING DKOS STRAIGHT DIN 20066/3865


| 227II SERIES | THREAD | HOSE | BORE | DIMENS | ONS (MM) |
|---------------------------|-----------|------|------|--------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S22711-14-04 | M14 x 1.5 | 6 | 4 | 19 | |
| S22711-16-04 | M16 x 1.5 | 6 | 4 | 19 | |
| S22711-18-04 | M18 x 1.5 | 6 | 4 | 22 | |
| S22711-16-05 | M16 x 1.5 | 8 | 5 | 19 | |
| S22711-20-05 | M20 x 1.5 | 8 | 5 | 24 | |
| S22711-18-06 | M18 x 1.5 | 10 | 6 | 22 | |
| S22711-20-06 | M20 x 1.5 | 10 | 6 | 24 | |
| S22711-22-06 | M22 x 1.5 | 10 | 6 | 27 | |
| S22711-24-06 | M24 x 1.5 | 10 | 6 | 30 | |
| S22711-20-08 | M20 x 1.5 | 12 | 8 | 24 | |
| S22711-22-08 | M22 x 1.5 | 12 | 8 | 27 | |
| S22711-24-08 | M24 x 1.5 | 12 | 8 | 30 | |
| S22711-30-10 | M30 x 2 | 16 | 10 | 36 | |
| S22711-30-12 | M30 x 2 | 19 | 12 | 36 | |
| S22711-36-12 | M36 x 2 | 19 | 12 | 46 | |
| S22711-42-12 | M42 x 2 | 19 | 12 | 50 | |
| S22711-36-16 | M36 x 2 | 25 | 16 | 46 | |
| S22711-42-16 | M42 x 2 | 25 | 16 | 50 | |
| S22711-52-20 | M52 x 2 | 32 | 20 | 60 | |
| S22711-52-24 | M52 x 2 | 38 | 24 | 60 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

METRIC FEMALE 24° CONE O-RING DKOS 45° ELBOW DIN 20066/3865







| 2274I SERIES | THREAD | HOSE BORE DIMENSIONS (| | DIMENSIONS (MM | | |
|---------------------------|-----------|------------------------|------|----------------|------|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | S 1 | Н | |
| S22741-14-04 | M14 x 1.5 | 6 | 4 | 19 | 17 | |
| S22741-16-04 | M16 x 1.5 | 6 | 4 | 19 | 17 | |
| S22741-18-04 | M18 x 1.5 | 6 | 4 | 22 | 17 | |
| S22741-16-05 | M16 x 1.5 | 8 | 5 | 19 | 17 | |
| S22741-18-06 | M18 x 1.5 | 10 | 6 | 22 | 17 | |
| S22741-20-06 | M20 x 1.5 | 10 | 6 | 24 | 18 | |
| S22741-22-06 | M22 x 1.5 | 10 | 6 | 27 | 21 | |
| S22741-20-08 | M20 x 1.5 | 12 | 8 | 24 | 18.5 | |
| S22741-22-08 | M22 x 1.5 | 12 | 8 | 27 | 21 | |
| \$22741-24-08 | M24 x 1.5 | 12 | 8 | 30 | 21 | |
| S22741-24-10 | M24 x 1.5 | 16 | 10 | 30 | 21 | |
| S22741-30-10 | M30 x 2 | 16 | 10 | 36 | 25 | |
| S22741-30-12 | M30 x 2 | 19 | 12 | 36 | 25 | |
| S22741-36-12 | M36 x 2 | 19 | 12 | 46 | 30.5 | |
| S22741-42-16 | M42 x 2 | 25 | 16 | 50 | 35.5 | |
| S22741-52-20 | M52 x 2 | 32 | 20 | 60 | 42 | |
| S22741-52-25 | M52 x 2 | 38 | 24 | 60 | 42 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



METRIC FEMALE 24° CONE O-RING DKOS 90° ELBOW DIN 20066/3865




| 2279I SERIES | THREAD | HOSE | BORE | DIMENSI | DIMENSIONS (MM) | |
|---------------------------|-----------|------|------|---------|-----------------|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н | |
| S22791-14-04 | M14 x 1.5 | 6 | 4 | 19 | 32 | |
| S22791-16-04 | M16 x 1.5 | 6 | 4 | 19 | 32 | |
| S22791-18-04 | M18 x 1.5 | 6 | 4 | 22 | 32 | |
| S22791-16-05 | M16 x 1.5 | 8 | 5 | 19 | 32 | |
| S22791-18-05 | M18 x 1.5 | 8 | 5 | 22 | 32 | |
| S22791-20-05 | M20 x 1.5 | 8 | 5 | 24 | 34 | |
| S22791-18-06 | M18 x 1.5 | 10 | 6 | 22 | 32 | |
| S22791-20-06 | M20 x 1.5 | 10 | 6 | 24 | 35.5 | |
| S22791-22-06 | M22 x 1.5 | 10 | 6 | 27 | 35.5 | |
| S22791-20-08 | M20 x 1.5 | 12 | 8 | 24 | 35.5 | |
| S22791-22-08 | M22 x 1.5 | 12 | 8 | 27 | 35.5 | |
| S22791-24-08 | M24 x 1.5 | 12 | 8 | 30 | 43 | |
| \$22791-30-08 | M30 x 2 | 12 | 8 | 36 | 49.5 | |
| S22791-24-10 | M24 x 1.5 | 16 | 10 | 30 | 43 | |
| S22791-30-10 | M30 x 2 | 16 | 10 | 36 | 49.5 | |
| S22791-30-12 | M30 x 2 | 19 | 12 | 36 | 49.5 | |
| S22791-36-12 | M36 x 2 | 19 | 12 | 46 | 59 | |
| S22791-42-16 | M42 x 2 | 25 | 16 | 50 | 70 | |
| S22791-52-20 | M52 x 2 | 32 | 20 | 60 | 87 | |
| S22791-52-24 | M52 x 2 | 38 | 24 | 60 | 87 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

METRIC MALE 24° CONE SEAT DKOS STRAIGHT DIN 20066/3861




| 12711 SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|-----------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | Е | DN | DASH | \$1 | |
| S12711-14-04 | M14 x 1.5 | 6 | 4 | 17 | |
| S12711-16-04 | M16 x 1.5 | 6 | 4 | 17 | |
| S12711-18-04 | M18 x 1.5 | 6 | 4 | 19 | |
| S12711-20-05 | M20 x 1.5 | 8 | 5 | 22 | |
| S12711-22-05 | M22 x 1.5 | 8 | 5 | 24 | |
| S12711-20-06 | M20 x 1.5 | 10 | 6 | 22 | |
| S12711-22-06 | M22 x 1.5 | 10 | 6 | 24 | |
| S12711-22-08 | M22 x 1.5 | 12 | 8 | 24 | |
| S12711-24-08 | M24 x 1.5 | 12 | 8 | 27 | |
| S12711-30-10 | M30 x 2 | 16 | 10 | 32 | |
| S12711-36-12 | M36 x 2 | 19 | 12 | 41 | |
| S12711-36-16 | M36 x 2 | 25 | 16 | 41 | |
| S12711-42-16 | M42 x 2 | 25 | 16 | 46 | |
| S12711-42-20 | M42 x 2 | 32 | 20 | 46 | |
| S12711-52-20 | M52 x 2 | 32 | 20 | 55 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


METRIC BANJO DIN 7642



| 722II SERIES | THREAD | HOSE | BORE | DIN | MENSIONS (M | 1M) |
|---------------------------|-----------|------|------|------|-------------|-----|
| PROPULSE FITTING PART NO. | E | DN | DASH | D | D | Н |
| \$72211-10-03 | M10 x 1 | 5 | 3 | 10.1 | 17 | 10 |
| \$72211-10-04 | M10 x 1 | 6 | 4 | 10.1 | 17 | 10 |
| \$72211-12-04 | M12 x 1.5 | 6 | 4 | 12.1 | 20 | 12 |
| \$72211-14-04 | M14 x 1.5 | 6 | 4 | 14.1 | 24 | 14 |
| \$72211-16-04 | M16 x 1.5 | 6 | 4 | 16.1 | 28 | 16 |
| \$72211-18-04 | M18 x 1.5 | 6 | 4 | 18.1 | 32 | 20 |
| \$72211-12-05 | M12 x 1.5 | 8 | 5 | 12.1 | 20 | 12 |
| \$72211-14-05 | M14 x 1.5 | 8 | 5 | 14.1 | 24 | 14 |
| \$72211-16-05 | M16 x 1.5 | 8 | 5 | 16.1 | 28 | 16 |
| \$72211-18-05 | M18 x 1.5 | 8 | 5 | 18.1 | 32 | 20 |
| \$72211-12-06 | M12 x 1.5 | 10 | 6 | 12.1 | 20 | 12 |
| \$72211-14-06 | M14 x 1.5 | 10 | 6 | 14.1 | 24 | 14 |
| \$72211-16-06 | M16 x 1.5 | 10 | 6 | 16.1 | 28 | 16 |
| S72211-18-06 | M18 x 1.5 | 10 | 6 | 18.1 | 32 | 20 |
| \$72211-22-06 | M22 x 1.5 | 10 | 6 | 22.1 | 39 | 25 |
| \$72211-18-08 | M18 x 1.5 | 12 | 8 | 18.1 | 32 | 20 |
| \$72211-22-08 | M22 x 1.5 | 12 | 8 | 22.1 | 39 | 25 |
| \$72211-22-10 | M22 x 1.5 | 16 | 10 | 22.1 | 39 | 25 |
| \$72211-26-12 | M26 x 1.5 | 19 | 12 | 26.1 | 46 | 30 |
| \$72211-30-16 | M30 x 1.5 | 25 | 16 | 30.1 | 54 | 36 |
| \$72211-30-20 | M30 x 1.5 | 32 | 20 | 30.1 | 54 | 36 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.


ORFS FEMALE SHORT STRAIGHT SAE J1453/J516



| 264IIS SERIES | THREAD | HOSI | E BORE | DIMENSI | ONS (MM) |
|---------------------------|---------------|------|--------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | \$2 |
| S26411S-04-04 | 9/16" x 18 | 6 | 4 | 13 | 17 |
| S26411S-06-04 | 11/16" x 16 | 6 | 4 | 17 | 22 |
| S26411S-04-05 | 9/16" x 18 | 8 | 5 | 17 | 19 |
| S26411S-06-05 | 11/16" x 16 | 8 | 5 | 17 | 22 |
| S26411S-08-05 | 13/16" x 16 | 8 | 5 | 19 | 24 |
| S26411S-04-06 | 9/16" x 18 | 10 | 6 | 13 | 17 |
| S26411S-06-06 | 11/16" x 16 | 10 | 6 | 17 | 22 |
| S26411S-08-06 | 13/16" x 16 | 10 | 6 | 22 | 24 |
| S26411S-06-08 | 11/16" x 16 | 12 | 8 | 17 | 22 |
| S26411S-08-08 | 13/16" x 16 | 12 | 8 | 22 | 24 |
| S26411S-10-08 | 1" x 14 | 12 | 8 | 24 | 30 |
| S26411S-12-08 | 1.3/16" x 12 | 12 | 8 | 28 | 36 |
| S26411S-08-10 | 13/16" x 16 | 16 | 10 | 22 | 24 |
| S26411S-10-10 | 1" x 14 | 16 | 10 | 24 | 30 |
| S26411S-12-10 | 1.3/16" x 12 | 16 | 10 | 28 | 36 |
| S26411S-10-12 | 1" x 14 | 19 | 12 | 24 | 30 |
| S26411S-12-12 | 1.3/16" x 12 | 19 | 12 | 28 | 36 |
| S26411S-16-12 | 1.7/16" x 12 | 19 | 12 | 36 | 41 |
| S26411S-12-16 | 1.3/16" x 12 | 25 | 16 | 28 | 36 |
| S26411S-16-16 | 1.7/16" x 12 | 25 | 16 | 36 | 41 |
| S26411S-20-16 | 1.11/16" x 12 | 25 | 16 | 41 | 50 |
| S26411S-16-20 | 1.7/16" x 12 | 32 | 20 | 36 | 41 |
| S26411S-20-20 | 1.11/16" x 12 | 32 | 20 | 41 | 50 |
| S26411S-24-20 | 2" x 12 | 32 | 20 | 50 | 60 |
| S26411S-20-24 | 1.11/16" x 12 | 38 | 24 | 41 | 50 |
| S26411S-24-24 | 2" x 12 | 38 | 24 | 50 | 60 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




ORFS FEMALE LONG STRAIGHT SAE J1453/J516


| 264IIL SERIES | THREAD | HOS | E BORE | DIMENS | IONS (MM) |
|---------------------------|---------------|-----|--------|--------|-----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | \$2 |
| S26411L-04-04 | 9/16" x 18 | 6 | 4 | 13 | 19 |
| S26411L-06-04 | 11/16" x 16 | 6 | 4 | 17 | 22 |
| S26411L-04-05 | 9/16" x 18 | 8 | 5 | 13 | 17 |
| S26411L-06-05 | 11/16" x 16 | 8 | 5 | 17 | 22 |
| S26411L-06-06 | 11/16" x 16 | 10 | 6 | 17 | 22 |
| S26411L-08-06 | 13/16" x 16 | 10 | 6 | 19 | 27 |
| S26411L-06-08 | 11/16" x 16 | 12 | 8 | 19 | 22 |
| S26411L-08-08 | 13/16" x 16 | 12 | 8 | 22 | 24 |
| S26411L-10-08 | 1" x 14 | 12 | 8 | 24 | 30 |
| S26411L-12-08 | 1.3/16" x 12 | 12 | 8 | 28 | 36 |
| S26411L-10-10 | 1" x 14 | 16 | 10 | 24 | 30 |
| S26411L-12-10 | 1.3/16" x 12 | 16 | 10 | 28 | 36 |
| S26411L-10-12 | 1" x 14 | 19 | 12 | 28 | 30 |
| S26411L-12-12 | 1.3/16" x 12 | 19 | 12 | 28 | 36 |
| S26411L-16-12 | 1.7/16" x 12 | 19 | 12 | 36 | 41 |
| S26411L-12-16 | 1.3/16" x 12 | 25 | 16 | 28 | 36 |
| S26411L-16-16 | 1.7/16" x 12 | 25 | 16 | 36 | 41 |
| S26411L-20-16 | 1.11/16" x 12 | 25 | 16 | 41 | 50 |
| S26411L-20-20 | 1.11/16" x 12 | 32 | 20 | 41 | 50 |
| S26411L-24-24 | 2" x 12 | 38 | 24 | 50 | 60 |
| S26411S-20-16 | 1.11/16" x 12 | 25 | 16 | 41 | 50 |
| S26411S-16-20 | 1.7/16" x 12 | 32 | 20 | 36 | 41 |
| S26411S-20-20 | 1.11/16" x 12 | 32 | 20 | 41 | 50 |
| S26411S-24-20 | 2" x 12 | 32 | 20 | 50 | 60 |
| S26411S-20-24 | 1.11/16" x 12 | 38 | 24 | 41 | 50 |
| S26411S-24-24 | 2" x 12 | 38 | 24 | 50 | 60 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ORFS FEMALE 45° ELBOW SAE J1453/J516







| 2644I SERIES | THREAD | HOSE BORE | DIMENSI | ONS (MM) |
|---------------------------|---------------|-----------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | \$1 | Н |
| S26441-04-04 | 9/16" x 18 | 6 | 19 | 10 |
| S26441-06-04 | 11/16" x 16 | 6 | 22 | 11 |
| S26441-04-05 | 9/16" x 18 | 8 | 19 | 10 |
| S26441-06-05 | 11/16" x 16 | 8 | 22 | 11 |
| S26441-04-06 | 9/16" x 18 | 10 | 19 | 10 |
| \$26441-06-06 | 11/16" x 16 | 10 | 22 | 11 |
| \$26441-08-06 | 13/16" x 16 | 10 | 24 | 15 |
| S26441-06-08 | 11/16" x 16 | 12 | 22 | 11 |
| S26441-08-08 | 13/16" x 16 | 12 | 24 | 15 |
| S26441-10-08 | 1" x 14 | 12 | 30 | 16 |
| S26441-12-08 | 1.3"/16 x 12 | 12 | 36 | 21 |
| S26441-08-10 | 13/16" x 16 | 16 | 24 | 15 |
| S26441-10-10 | 1" x 14 | 16 | 30 | 16 |
| S26441-12-10 | 1.3/16" x 12 | 16 | 36 | 21 |
| S26441-10-12 | 1" x 14 | 19 | 30 | 16 |
| S26441-12-12 | 1.3/16" x 12 | 19 | 36 | 21 |
| S26441-16-12 | 1.7/16" x 12 | 19 | 41 | 24 |
| S26441-12-16 | 1.3/16" x 12 | 25 | 36 | 21 |
| S26441-16-16 | 1.7/16" x 12 | 25 | 41 | 24 |
| S26441-20-16 | 1.11/16" x 12 | 25 | 50 | 25 |
| S26441-16-20 | 1.7/16" x 12 | 32 | 41 | 24 |
| S26441-20-20 | 1.11/16" x 12 | 32 | 50 | 25 |
| S26441-24-20 | 2" x 12 | 32 | 60 | 27 |
| S26441-20-24 | 1.11/16" x 12 | 38 | 50 | 25 |
| S26441-24-24 | 2" x 12 | 38 | 60 | 27 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



ORFS FEMALE 90° ELBOW SAE J1453/J516





| 2649I SERIES | THREAD | THREAD HOSE BORE | | | ONS (MM) |
|---------------------------|---------------|------------------|------|-----|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | Н |
| S26491-04-04 | 9/16" x 18 | 6 | 4 | 19 | 21 |
| \$26491-06-04 | 11/16" x 16 | 6 | 4 | 22 | 23 |
| S26491-04-05 | 9/16" x 18 | 8 | 5 | 19 | 21 |
| S26491-06-05 | 11/16" x 16 | 8 | 5 | 22 | 23 |
| S26491-04-06 | 9/16" x 18 | 10 | 6 | 19 | 21 |
| S26491-06-06 | 11/16" x 16 | 10 | 6 | 22 | 23 |
| S26491-08-06 | 13/16" x 16 | 10 | 6 | 24 | 29 |
| \$26491-06-08 | 11/16" x 16 | 12 | 8 | 22 | 23 |
| S26491-08-08 | 13/16" x 16 | 12 | 8 | 24 | 29 |
| S26491-10-08 | 1" x 14 | 12 | 8 | 30 | 32 |
| S26491-08-10 | 13"/16 x 16 | 16 | 10 | 24 | 29 |
| \$26491-10-10 | 1" x 14 | 16 | 10 | 30 | 32 |
| S26491-12-10 | 1.3/16" x 12 | 16 | 10 | 36 | 48 |
| S26491-10-12 | 1" x 14 | 19 | 12 | 30 | 32 |
| S26491-12-12 | 1.3/16" x 12 | 19 | 12 | 36 | 48 |
| S26491-16-12 | 1.7/16" x 12 | 19 | 12 | 41 | 56 |
| S26491-12-16 | 1.3/16" x 12 | 25 | 16 | 36 | 48 |
| S26491-16-16 | 1.7/16" x 12 | 25 | 16 | 41 | 56 |
| S26491-20-16 | 1.11/16" x 12 | 25 | 16 | 50 | 64 |
| S26491-16-20 | 1.7/16" x 12 | 32 | 20 | 41 | 56 |
| S26491-20-20 | 1.11/16" x 12 | 32 | 20 | 50 | 64 |
| S26491-24-20 | 2" x 12 | 32 | 20 | 60 | 69 |
| S26491-20-24 | 1.11/16" x 12 | 38 | 24 | 50 | 64 |
| S26491-24-24 | 2" x 12 | 38 | 24 | 60 | 69 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

ORFS FEMALE 90° ELBOW MEDIUM DROP SAE J1453/J516







| 2649IM SERIES | THREAD | THREAD HOSE BORE | | DIMENSIONS (M | |
|---------------------------|---------------|------------------|------|---------------|----|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н |
| S26491M-04-04 | 9/16" x 18 | 6 | 4 | 19 | 32 |
| S26491M-06-04 | 11/16" x 16 | 6 | 4 | 22 | 38 |
| S26491M-06-06 | 11/16" x 16 | 10 | 6 | 22 | 38 |
| S26491M-08-06 | 13/16" x 16 | 10 | 6 | 24 | 41 |
| S26491M-08-08 | 13/16" x 16 | 12 | 8 | 24 | 41 |
| S26491M-10-08 | 1" x 14 | 12 | 8 | 30 | 47 |
| S26491M-10-10 | 1" x 14 | 16 | 10 | 30 | 47 |
| S26491M-10-12 | 1" x 14 | 19 | 12 | 30 | 47 |
| S26491M-12-12 | 1.3/16" x 12 | 19 | 12 | 36 | 58 |
| S26491M-16-16 | 1.7/16" x 12 | 25 | 16 | 41 | 71 |
| S26491M-20-20 | 1.11/16" x 12 | 32 | 20 | 50 | 78 |
| S26491M-24-24 | 2" x 12 | 38 | 24 | 60 | 86 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



ORFS FEMALE 90° ELBOW LONG DROP SAE J1453/J516




| 2649IL SERIES | THREAD | THREAD HOSE BORE | | DIMENSIONS (MM | |
|---------------------------|---------------|------------------|------|----------------|-----|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н |
| S26491L-04-04 | 9/16" x 18 | 6 | 4 | 17 | 46 |
| S26491L-06-06 | 11/16" x 16 | 10 | 6 | 22 | 54 |
| S26491L-08-06 | 13/16" x 16 | 10 | 6 | 24 | 64 |
| S26491L-08-08 | 13/16" x 16 | 12 | 8 | 24 | 64 |
| S26491L-10-08 | 1" x 14 | 12 | 8 | 30 | 70 |
| S26491L-10-10 | 1" x 14 | 16 | 10 | 30 | 70 |
| S26491L-10-12 | 1" x 14 | 19 | 12 | 30 | 70 |
| S26491L-12-12 | 1.3/16" x 12 | 19 | 12 | 36 | 96 |
| S26491L-16-16 | 1.7/16" x 12 | 25 | 16 | 41 | 114 |
| S26491L-20-20 | 1.11/16" x 12 | 31 | 20 | 50 | 129 |
| S26491L-24-24 | 2" x 12 | 38 | 24 | 60 | 141 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


ORFS MALE STRAIGHT SAE J1453/J516




| 16411 SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|---------------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | |
| S16411-04-04 | 9/16" x 18 | 6 | 4 | 17 | |
| \$16411-06-04 | 11/16" x 16 | 6 | 4 | 19 | |
| S16411-06-06 | 11/16" x 16 | 10 | 6 | 19 | |
| S16411-08-06 | 13/16" x 16 | 10 | 6 | 22 | |
| S16411-08-08 | 13/16" x 16 | 12 | 8 | 22 | |
| S16411-10-08 | 1" x 14 | 12 | 8 | 27 | |
| S16411-12-08 | 1.3/16" x 12 | 12 | 8 | 32 | |
| S16411-08-10 | 13/16" x 16 | 16 | 10 | 22 | |
| S16411-10-10 | 1" x 14 | 16 | 10 | 27 | |
| S16411-12-10 | 1.3/16" x 12 | 16 | 10 | 32 | |
| S16411-12-12 | 1.3/16" x 12 | 19 | 12 | 32 | |
| S16411-16-12 | 1.7/16" x 12 | 19 | 12 | 41 | |
| S16411-16-16 | 1.7/16" x 12 | 25 | 16 | 41 | |
| S16411-20-20 | 1.11/16" x 12 | 32 | 20 | 46 | |
| S16411-24-24 | 2" x 12 | 38 | 24 | 55 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



JIC FEMALE 37° CONE DOUBLE HEX STRAIGHT SAE J514/J516





| 289IID SERIES | THREAD | HOS | E BORE | DIMENSIONS (MM) | | |
|---------------------------|--------------|-----|--------|-----------------|-----|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | \$2 | |
| S28911D-03-04 | 7/16" x 20 | 6 | 4 | 16 | 14 | |
| S28911D-04-03 | 7/16" x 20 | 5 | 3 | 14 | 14 | |
| S28911D-04-04 | 7/16" x 20 | 6 | 4 | 14 | 14 | |
| S28911D-05-04 | 1/2" x 20 | 6 | 4 | 17 | 17 | |
| S28911D-06-04 | 9/16" x 18 | 6 | 4 | 19 | 19 | |
| S28911D-05-05 | 1/2" x 20 | 8 | 5 | 17 | 17 | |
| S28911D-06-05 | 9/16" x 18 | 8 | 5 | 17 | 19 | |
| S28911D-08-05 | 3/4" x 16 | 8 | 5 | 19 | 24 | |
| S28911D-04-06 | 7/16" x 20 | 10 | 6 | 17 | 17 | |
| S28911D-05-06 | 1/2" x 20 | 10 | 6 | 17 | 17 | |
| S28911D-06-06 | 9/16" x 18 | 10 | 6 | 19 | 19 | |
| S28911D-08-06 | 3/4" x 16 | 10 | 6 | 19 | 24 | |
| S28911D-10-06 | 7/8" x 14 | 10 | 6 | 22 | 27 | |
| S28911D-06-08 | 9/16" x 18 | 12 | 8 | 19 | 19 | |
| S28911D-08-08 | 3/4" x 16 | 12 | 8 | 22 | 24 | |
| S28911D-10-08 | 7/8" x 14 | 12 | 8 | 22 | 27 | |
| S28911D-12-08 | 1.1/16" x 12 | 12 | 8 | 27 | 32 | |
| S28911D-08-10 | 3/4" x 16 | 16 | 10 | 24 | 24 | |
| S28911D-10-10 | 7/8" x 14 | 16 | 10 | 24 | 27 | |
| S28911D-12-10 | 1.1/16" x 12 | 16 | 10 | 27 | 32 | |
| S28911D-08-12 | 3/4" x 16 | 19 | 12 | 24 | 24 | |
| S28911D-10-12 | 7/8" x 14 | 19 | 12 | 27 | 27 | |
| S28911D-12-12 | 1.1/16" x 12 | 19 | 12 | 27 | 32 | |
| S28911D-16-12 | 1.5/16" x 12 | 19 | 12 | 32 | 41 | |
| S28911D-12-16 | 1.1/16" x 12 | 25 | 16 | 32 | 32 | |
| S28911D-16-16 | 1.5/16" x 12 | 25 | 16 | 41 | 41 | |
| S28911D-20-16 | 1.5/8" x 12 | 25 | 16 | 41 | 50 | |
| S28911D-20-20 | 1.5/8" x 12 | 32 | 20 | 50 | 50 | |
| S28911D-24-24 | 1.7/8" x 12 | 38 | 24 | 60 | 60 | |
| S28911D-32-32 | 2.1/2" x 12 | 50 | 32 | 75 | 75 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

JIC FEMALE 37° CONE 45° ELBOW SAE J514/J516







| 2894I SERIES | THREAD | HOSI | BORE | DIMENSIONS (MM) | |
|---------------------------|--------------|------|------|-----------------|----|
| PROPULSE FITTING PART NO. | Е | DN | DASH | \$1 | Н |
| S28941-04-03 | 7/16" x 20 | 5 | 3 | 17 | 10 |
| S28941-04-04 | 7/16" x 20 | 6 | 4 | 17 | 10 |
| S28941-05-04 | 1/2" x 20 | 6 | 4 | 17 | 10 |
| S28941-06-04 | 9/16" x 18 | 6 | 4 | 19 | 11 |
| S28941-05-05 | 1/2" x 20 | 8 | 5 | 17 | 10 |
| S28941-06-05 | 9/16" x 18 | 8 | 5 | 19 | 11 |
| S28941-05-06 | 1/2" x 20 | 10 | 6 | 17 | 10 |
| S28941-06-06 | 9/16" x 18 | 10 | 6 | 19 | 11 |
| S28941-08-06 | 3/4" x 16 | 10 | 6 | 24 | 15 |
| S28941-06-08 | 9/16" x 18 | 12 | 8 | 19 | 11 |
| \$28941-08-08 | 3/4" x 16 | 12 | 8 | 24 | 15 |
| S28941-10-08 | 7/8" x 14 | 12 | 8 | 27 | 16 |
| S28941-12-08 | 1.1/16" x 12 | 12 | 8 | 32 | 21 |
| S28941-10-10 | 7/8" x 14 | 16 | 10 | 27 | 16 |
| S28941-12-10 | 1.1/16" x 12 | 16 | 10 | 32 | 21 |
| S28941-10-12 | 7/8" x 14 | 19 | 12 | 27 | 16 |
| S28941-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | 21 |
| S28941-14-12 | 1.3/16" x 12 | 19 | 12 | 36 | 21 |
| S28941-16-12 | 1.5/16" x 12 | 19 | 12 | 41 | 24 |
| S28941-12-16 | 1.1/16" x 12 | 25 | 16 | 32 | 21 |
| S28941-16-16 | 1.5/16" x 12 | 25 | 16 | 41 | 24 |
| S28941-16-20 | 1.5/16" x 12 | 32 | 20 | 41 | 24 |
| S28941-20-20 | 1.5/8" x 12 | 32 | 20 | 50 | 25 |
| S28941-24-20 | 1.7/8" x 12 | 32 | 20 | 60 | 27 |
| S28941-24-24 | 1.7/8" x 12 | 38 | 24 | 60 | 27 |
| S28941-32-32 | 2.1/2" x 12 | 50 | 32 | 75 | 34 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



JIC FEMALE 37° CONE 90° ELBOW SAE J514/J516





| 2899I SERIES | THREAD | HOS | E BORE | DIMENSI | ONS (MM) |
|---------------------------|--------------|-----|--------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н |
| S28991-04-04 | 7/16" x 20 | 6 | 4 | 17 | 21 |
| \$28991-05-04 | 1/2" x 20 | 6 | 4 | 17 | 21 |
| S28991-06-04 | 9/16" x 18 | 6 | 4 | 19 | 23 |
| S28991-05-05 | 1/2" x 20 | 8 | 5 | 17 | 21 |
| S28991-06-05 | 9/16" x 18 | 8 | 5 | 19 | 23 |
| S28991-05-06 | 1/2" x 20 | 10 | 6 | 17 | 21 |
| S28991-06-06 | 9/16" x 18 | 10 | 6 | 19 | 23 |
| S28991-08-06 | 3/4" x 16 | 10 | 6 | 24 | 29 |
| S28991-06-08 | 9/16" x 18 | 12 | 8 | 19 | 23 |
| S28991-08-08 | 3/4" x 16 | 12 | 8 | 24 | 29 |
| S28991-10-08 | 7/8" x 14 | 12 | 8 | 27 | 32 |
| S28991-12-08 | 1.1/16" x 12 | 12 | 8 | 32 | 48 |
| S28991-08-10 | 3/4" x 16 | 16 | 10 | 24 | 29 |
| S28991-10-10 | 7/8" x 14 | 16 | 10 | 27 | 32 |
| S28991-12-10 | 1.1/16" x 12 | 16 | 10 | 32 | 48 |
| S28991-10-12 | 7/8" x 14 | 19 | 12 | 27 | 32 |
| S28991-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | 48 |
| S28991-14-12 | 1.3/16" x 12 | 19 | 12 | 36 | 51 |
| S28991-16-12 | 1.5/16" x 12 | 19 | 12 | 41 | 56 |
| S28991-12-16 | 1.1/16" x 12 | 25 | 16 | 32 | 48 |
| S28991-16-16 | 1.5/16" x 12 | 25 | 16 | 41 | 56 |
| \$28991-20-16 | 1.5/8" x 12 | 25 | 16 | 50 | 60 |
| S28991-16-20 | 1.5/16" x 12 | 32 | 20 | 41 | 56 |
| \$28991-20-20 | 1.5/8" x 12 | 32 | 20 | 50 | 64 |
| S28991-24-20 | 1.7/8" x 12 | 32 | 20 | 60 | 69 |
| \$28991-24-24 | 1.7/8" x 12 | 38 | 24 | 60 | 69 |
| S28991-32-32 | 2.1/2" x 12 | 50 | 32 | 75 | 88 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

JIC FEMALE 37° CONE 90° ELBOW MEDIUM DROP SAE J514/J516







| 2899IM SERIES | THREAD | THREAD HOSE BORE | | | DIMENSIONS (MM) | |
|---------------------------|--------------|------------------|------|-----|-----------------|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | Н | |
| S28991M-04-04 | 7/16" x 20 | 6 | 4 | 17 | 32 | |
| S28991M-06-06 | 9/16" x 18 | 10 | 6 | 19 | 38 | |
| S28991M-08-06 | 3/4" x 16 | 10 | 6 | 24 | 41 | |
| S28991M-08-08 | 3/4" x 16 | 12 | 8 | 24 | 41 | |
| S28991M-12-10 | 1.1/16" x 12 | 16 | 10 | 32 | 58 | |
| S28991M-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | 58 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




JIC FEMALE 37° CONE 90° ELBOW LONG DROP SAE J514/J516



| 2899IL SERIES | THREAD | HOSE BORE | | DIMENSIONS (MM) | | |
|---------------------------|--------------|-----------|------|-----------------|-----|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | Н | |
| S28991L-04-04 | 7/16" x 20 | 6 | 4 | 17 | 46 | |
| S28991L-05-04 | 1/2" x 20 | 6 | 4 | 17 | 46 | |
| S28991L-06-06 | 9/16" x 18 | 10 | 6 | 19 | 54 | |
| S28991L-08-06 | 3/4" x 16 | 10 | 6 | 24 | 64 | |
| S28991L-08-08 | 3/4" x 16 | 12 | 8 | 24 | 64 | |
| S28991L-10-10 | 7/8" x 14 | 16 | 10 | 27 | 70 | |
| S28991L-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | 93 | |
| S28991L-14-12 | 1.3/16" x 12 | 19 | 12 | 36 | 100 | |
| S28991L-16-16 | 1.5/16" x 12 | 25 | 16 | 41 | 114 | |
| S28991L-20-20 | 1.5/8" x 12 | 32 | 20 | 50 | 129 | |
| S28991L-24-24 | 1.7/8" x 12 | 38 | 24 | 60 | 141 | |
| S28991L-32-32 | 2.1/2" x 12 | 50 | 32 | 75 | 222 | |

 $[\]hbox{*Dimensions provided are nominal for reference only and may vary based on current supply.}$

JIC MALE 37° CONE STRAIGHT SAE J514/J516




| 18911 SERIES | THREAD | HOSE | BORE | DIMENS | IONS (MM) |
|---------------------------|--------------|------|------|--------|-----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S18911-04-03 | 7/16" x 20 | 5 | 3 | 14 | |
| S18911-04-04 | 7/16" x 20 | 6 | 4 | 14 | |
| S18911-05-04 | 1/2" x 20 | 6 | 4 | 14 | |
| S18911-06-04 | 9/16" x 18 | 6 | 4 | 17 | |
| S18911-05-05 | 1/2" x 20 | 8 | 5 | 14 | |
| S18911-06-05 | 9/16" x 18 | 8 | 5 | 17 | |
| S18911-05-06 | 1/2" x 20 | 10 | 6 | 17 | |
| S18911-06-06 | 9/16" x 18 | 10 | 6 | 17 | |
| S18911-08-06 | 3/4" x 16 | 10 | 6 | 22 | |
| S18911-10-06 | 7/8" x 14 | 10 | 6 | 24 | |
| S18911-08-08 | 3/4" x 16 | 12 | 8 | 22 | |
| S18911-10-08 | 7/8" x 14 | 12 | 8 | 24 | |
| S18911-12-08 | 1.1/16" x 12 | 12 | 8 | 27 | |
| S18911-10-10 | 7/8" x 14 | 16 | 10 | 24 | |
| S18911-12-10 | 1.1/16" x 12 | 16 | 10 | 27 | |
| S18911-14-10 | 1.3/16" x 12 | 16 | 10 | 32 | |
| S18911-12-12 | 1.1/16" x 12 | 19 | 12 | 27 | |
| S18911-14-12 | 1.3/16" x 12 | 19 | 12 | 32 | |
| S18911-16-12 | 1.5/16" x 12 | 19 | 12 | 36 | |
| S18911-12-16 | 1.1/16" x 12 | 25 | 16 | 27 | |
| S18911-16-16 | 1.5/16" x 12 | 25 | 16 | 36 | |
| S18911-20-16 | 1.5/8" x 12 | 25 | 16 | 46 | |
| S18911-20-20 | 1.5/8" x 12 | 32 | 20 | 46 | |
| S18911-24-20 | 1.7/8" x 12 | 32 | 20 | 50 | |
| S18911-24-24 | 1.7/8" x 12 | 38 | 24 | 50 | |
| S18911-32-32 | 2.1/2" x 12 | 50 | 32 | 65 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NPSM FEMALE 30° CONE STRAIGHT




| 238II SERIES | THREAD | HOSE BORE | | DIMENSION | IS (MM) |
|---------------------------|---------------|-----------|------|-----------|---------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S23811-04-03 | 1/4" x 18 | 5 | 3 | 19 | |
| S23811-04-04 | 1/4" x 18 | 6 | 4 | 19 | |
| \$23811-06-04 | 3/8" x 18 | 6 | 4 | 22 | |
| \$23811-06-05 | 3/8" x 18 | 8 | 5 | 22 | |
| S23811-04-06 | 1/4" x 18 | 10 | 6 | 19 | |
| S23811-06-06 | 3/8" x 18 | 10 | 6 | 22 | |
| S23811-08-08 | 1/2" x 14 | 12 | 8 | 27 | |
| \$23811-12-10 | 3/4" x 14 | 16 | 10 | 32 | |
| \$23811-12-12 | 3/4" x 14 | 19 | 12 | 32 | |
| \$23811-16-12 | 1" x 11.5 | 19 | 12 | 41 | |
| S23811-16-16 | 1" x 11.5 | 25 | 16 | 41 | |
| S23811-20-20 | 1.1/4" x 11.5 | 32 | 20 | 50 | |
| S23811-24-20 | 1.1/2" x 11.5 | 32 | 20 | 55 | |
| S23811-24-24 | 1.1/2" x 11.5 | 38 | 24 | 55 | |
| S23811-32-32 | 2" x 11.5 | 50 | 32 | 70 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


NPTF MALE 30° CONE STRAIGHT SAE J516



| 17811 SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|---------------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S17811-02-03 | 1/8" x 27 | 5 | 3 | 14 | |
| S17811-04-03 | 1/4" x 18 | 5 | 3 | 14 | |
| S17811-02-04 | 1/8" x 27 | 6 | 4 | 14 | |
| \$17811-04-04 | 1/4" x 18 | 6 | 4 | 14 | |
| S17811-06-04 | 3/8" x 18 | 6 | 4 | 19 | |
| S17811-08-04 | 1/2" x 14 | 6 | 4 | 22 | |
| S17811-04-05 | 1/4" x 18 | 8 | 5 | 17 | |
| S17811-06-05 | 3/8" x 18 | 8 | 5 | 19 | |
| S17811-04-06 | 1/4" x 18 | 10 | 6 | 17 | |
| S17811-06-06 | 3/8" x 18 | 10 | 6 | 19 | |
| S17811-08-06 | 1/2" x 14 | 10 | 6 | 22 | |
| S17811-06-08 | 3/8" x 18 | 12 | 8 | 22 | |
| S17811-08-08 | 1/2" x 14 | 12 | 8 | 22 | |
| \$17811-12-08 | 3/4" x 14 | 12 | 8 | 27 | |
| S17811-08-10 | 1/2" x 14 | 16 | 10 | 22 | |
| S17811-12-10 | 3/4" x 14 | 16 | 10 | 27 | |
| S17811-16-10 | 1" x 11.5 | 16 | 10 | 36 | |
| S17811-12-12 | 3/4" x 14 | 19 | 12 | 27 | |
| S17811-16-12 | 1" x 11.5 | 19 | 12 | 36 | |
| S17811-12-16 | 3/4" x 14 | 25 | 16 | 27 | |
| S17811-16-16 | 1" x 11.5 | 25 | 16 | 36 | |
| S17811-20-16 | 1.1/4" x 11.5 | 25 | 16 | 46 | |
| S17811-20-20 | 1.1/4" x 11.5 | 32 | 20 | 46 | |
| S17811-24-24 | 1.1/2" x 11.5 | 38 | 24 | 50 | |
| S17811-32-32 | 2" x 11.5 | 50 | 32 | 65 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




NPTF SWIVEL MALE 30° CONE STRAIGHT SAE J516

| 17811W SERIES | THREAD | HOSI | DIMENSI | ONS (MM) | |
|---------------------------|-----------|------|---------|----------|--|
| PROPULSE FITTING PART NO. | Е | DN | DASH | \$1 | |
| S17811W-02-04 | 1/8" x 27 | 6 | 4 | 14 | |
| S17811W-04-04 | 1/4" x 18 | 6 | 4 | 17 | |
| S17811W-06-04 | 3/8" x 18 | 6 | 4 | 19 | |
| S17811W-06-05 | 3/8" x 18 | 8 | 5 | 19 | |
| S17811W-04-06 | 1/4" x 18 | 10 | 6 | 17 | |
| \$17811W-06-06 | 3/8" x 18 | 10 | 6 | 19 | |
| S17811W-08-06 | 1/2" x 14 | 10 | 6 | 22 | |
| S17811W-08-08 | 1/2" x 14 | 12 | 8 | 22 | |
| S17811W-12-12 | 3/4" x 14 | 19 | 12 | 27 | |
| S17811W-16-16 | 1" x 11.5 | 25 | 16 | 36 | |

*Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

NPT FEMALE SOLID STRAIGHT




| 278II SERIES | THREAD | HOSE | BORE | DIMENSIONS (MM) | | |
|---------------------------|-----------|------|------|-----------------|--|--|
| PROPULSE FITTING PART NO. | Е | DN | DASH | \$1 | | |
| S27811-04-04 | 1/4" x 18 | 6 | 4 | 19 | | |
| S27811-04-06 | 1/4" x 18 | 10 | 6 | 19 | | |
| S27811-06-06 | 3/8" x 18 | 10 | 6 | 22 | | |
| S27811-08-06 | 1/2" x 14 | 10 | 6 | 25.4 | | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BSP FEMALE 60° CONE STRAIGHT





| 248II SERIES | THREAD | HOSI | BORE | DIMENSIONS (MM) | |
|---------------------------|-------------|------|------|-----------------|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S24811-02-03 | 1/8" x 28 | 5 | 3 | 14 | |
| S24811-04-03 | 1/4" x 19 | 5 | 3 | 19 | |
| S24811-02-04 | 1/8" x 28 | 6 | 4 | 14 | |
| S24811-04-04 | 1/4" x 19 | 6 | 4 | 19 | |
| S24811-06-04 | 3/8" x 19 | 6 | 4 | 22 | |
| S24811-04-05 | 1/4" x 19 | 8 | 5 | 19 | |
| S24811-06-05 | 3/8" x 19 | 8 | 5 | 22 | |
| S24811-04-06 | 1/4" x 19 | 10 | 6 | 19 | |
| S24811-06-06 | 3/8" x 19 | 10 | 6 | 22 | |
| S24811-08-06 | 1/2" x 14 | 10 | 6 | 27 | |
| S24811-06-08 | 3/8" x 14 | 12 | 8 | 22 | |
| S24811-08-08 | 1/2" x 14 | 12 | 8 | 27 | |
| S24811-10-08 | 5/8" x 14 | 12 | 8 | 30 | |
| S24811-12-08 | 3/4" x 14 | 12 | 8 | 32 | |
| S24811-10-10 | 5/8" x 14 | 16 | 10 | 30 | |
| S24811-12-10 | 3/4" x 14 | 16 | 10 | 32 | |
| S24811-12-12 | 3/4" x 14 | 19 | 12 | 32 | |
| S24811-16-12 | 1" x 11 | 19 | 12 | 41 | |
| S24811-16-16 | 1" x 11 | 25 | 16 | 41 | |
| S24811-20-16 | 1.1/4" x 11 | 32 | 16 | 50 | |
| S24811-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | |
| S24811-24-20 | 1.1/2" x 11 | 32 | 20 | 60 | |
| S24811-24-24 | 1.1/2" x 11 | 38 | 24 | 60 | |
| S24811-32-24 | 2" x 11 | 38 | 24 | 70 | |
| S24811-32-32 | 2" x 11 | 50 | 32 | 70 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BSP FEMALE 60° CONE 45° ELBOW






| 2484I SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|-------------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | \$1 | Н |
| S24841-04-04 | 1/4" x 19 | 6 | 4 | 19 | 15 |
| S24841-06-04 | 3/8" x 19 | 6 | 4 | 22 | 16 |
| S24841-06-05 | 3/8" x 19 | 8 | 5 | 22 | 15 |
| S24841-06-06 | 3/8" x 19 | 10 | 6 | 22 | 15 |
| S24841-08-06 | 1/2" x 14 | 10 | 6 | 27 | 16 |
| S24841-08-08 | 1/2" x 14 | 12 | 8 | 27 | 17 |
| S24841-10-08 | 5/8" x 14 | 12 | 8 | 30 | 22.5 |
| S24841-12-08 | 3/4" x 14 | 12 | 8 | 32 | 26 |
| S24841-10-10 | 5/8" x 14 | 16 | 10 | 30 | 26 |
| S24841-12-10 | 3/4" x 14 | 16 | 10 | 32 | 27 |
| S24841-12-12 | 3/4" x 14 | 19 | 12 | 32 | 28 |
| S24841-16-12 | 1" x 11 | 19 | 12 | 41 | 30 |
| S24841-16-16 | 1" x 11 | 25 | 16 | 41 | 37 |
| S24841-20-16 | 1.1/4" x 11 | 25 | 16 | 50 | 31 |
| S24841-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | 39 |
| 524841-24-24 | 1.1/2" x 11 | 38 | 24 | 60 | 45 |
| S24841-32-32 | 2" x 11 | 50 | 32 | 70 | 47 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

<u>S1</u>

BSP FEMALE 60° CONE 90° ELBOW




| 2489I SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|-------------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | Н |
| S24891-04-04 | 1/4" x 19 | 6 | 4 | 19 | 29 |
| S24891-06-04 | 3/8" x 19 | 6 | 4 | 22 | 31 |
| S24891-04-05 | 1/4" x 19 | 8 | 5 | 19 | 29.5 |
| S24891-06-05 | 3/8" x 19 | 8 | 5 | 22 | 27.5 |
| S24891-04-06 | 1/4" x 19 | 10 | 6 | 17 | 31.5 |
| S24891-06-06 | 3/8" x 19 | 10 | 6 | 22 | 31.5 |
| S24891-08-06 | 1/2" x 14 | 10 | 6 | 27 | 32 |
| S24891-06-08 | 3/8" x 19 | 12 | 8 | 22 | 41 |
| S24891-08-08 | 1/2" x 14 | 12 | 8 | 27 | 36 |
| S24891-10-08 | 5/8" x 14 | 12 | 8 | 30 | 44 |
| S24891-12-08 | 3/4" x 14 | 12 | 8 | 32 | 45.5 |
| S24891-08-10 | 1/2" x 14 | 16 | 10 | 27 | 55 |
| S24891-10-10 | 5/8" x 14 | 16 | 10 | 30 | 53.5 |
| S24891-12-10 | 3/4" x 14 | 16 | 10 | 32 | 55 |
| S24891-12-12 | 3/4" x 14 | 19 | 12 | 32 | 60 |
| S24891-16-12 | 1" x 11 | 19 | 12 | 41 | 62 |
| S24891-16-16 | 1" x 11 | 25 | 16 | 41 | 76 |
| S24891-20-16 | 1.1/4" x 11 | 25 | 16 | 50 | 78 |
| S24891-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | 84 |
| S24891-20-24 | 1.1/4" x 11 | 38 | 24 | 70 | 90 |
| S24891-24-24 | 1.1/2" x 11 | 38 | 24 | 60 | 99 |
| S24891-32-24 | 2" x 11 | 40 | 24 | 70 | 125 |
| S24891-32-32 | 2" x 11 | 50 | 32 | 70 | 110 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BSP MALE 60° CONE STRAIGHT




| 148II SERIES | THREAD | HOSE | BORE | DIMENSIO | NS (MM) |
|---------------------------|-------------|------|------|----------|---------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S14811-02-03 | 1/8" x 28 | 5 | 3 | 14 | |
| S14811-02-04 | 1/8" x 28 | 6 | 4 | 14 | |
| S14811-04-04 | 1/4" x 19 | 6 | 4 | 19 | |
| S14811-06-04 | 3/8" x 19 | 6 | 4 | 22 | |
| \$14811-06-05 | 3/8" x 19 | 8 | 5 | 22 | |
| \$14811-04-06 | 1/4" x 19 | 10 | 6 | 19 | |
| \$14811-06-06 | 3/8" x 19 | 10 | 6 | 22 | |
| \$14811-08-06 | 1/2" x 14 | 10 | 6 | 27 | |
| \$14811-06-08 | 3/8" x 19 | 12 | 8 | 22 | |
| \$14811-08-08 | 1/2" x 14 | 12 | 8 | 27 | |
| S14811-10-08 | 5/8" x 14 | 12 | 8 | 30 | |
| \$14811-12-08 | 3/4" x 14 | 12 | 8 | 32 | |
| \$14811-10-10 | 5/8" x 14 | 16 | 10 | 30 | |
| S14811-12-10 | 3/4" x 14 | 16 | 10 | 32 | |
| S14811-12-12 | 3/4" x 14 | 19 | 12 | 32 | |
| \$14811-16-12 | 1" x 11 | 19 | 12 | 41 | |
| S14811-16-16 | 1" x 11 | 25 | 16 | 41 | |
| S14811-20-16 | 1.1/4" x 11 | 25 | 16 | 50 | |
| S14811-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | |
| S14811-24-20 | 1.1/2" x 11 | 32 | 20 | 60 | |
| S14811-24-24 | 1.1/2" x 11 | 38 | 24 | 60 | |
| \$14811-32-32 | 2" x 11 | 50 | 32 | 70 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BSPP MALE O-RING FLAT SEAL STRAIGHT




| 14411 SERIES | THREAD | HOSE BORE | | DIMENSIONS (MM | |
|---------------------------|-------------|-----------|------|----------------|--|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S14411-04-04 | 1/4" x 19 | 6 | 4 | 17 | |
| S14411-08-04 | 1/2" x 14 | 6 | 4 | 27 | |
| S14411-04-06 | 1/4" x 19 | 10 | 6 | 19 | |
| S14411-06-06 | 3/8" x 19 | 10 | 6 | 22 | |
| S14411-08-06 | 1/2" x 14 | 10 | 6 | 27 | |
| \$14411-08-08 | 1/2" x 14 | 12 | 8 | 27 | |
| \$14411-10-10 | 5/8" x 14 | 16 | 10 | 30 | |
| S14411-12-10 | 3/4" x 14 | 16 | 10 | 32 | |
| S14411-12-12 | 3/4" x 14 | 19 | 12 | 32 | |
| S14411-12-16 | 3/4" x 14 | 25 | 16 | 32 | |
| S14411-16-16 | 1" x 11 | 25 | 16 | 41 | |
| S14411-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | |

▲ **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

BSP FEMALE FLAT SEAL STRAIGHT




| 244II SERIES | THREAD | HOSI | BORE | DIMENSIONS (MM) | |
|---------------------------|-------------|------|------|-----------------|--|
| PROPULSE FITTING PART NO. | Е | DN | DASH | \$1 | |
| S24411-04-04 | 1/4" x 19 | 6 | 4 | 19 | |
| S24411-06-04 | 3/8" x 19 | 6 | 4 | 22 | |
| S24411-06-05 | 3/8" x 19 | 8 | 5 | 22 | |
| S24411-04-06 | 1/4" x 19 | 10 | 6 | 19 | |
| S24411-06-06 | 3/8" x 19 | 10 | 6 | 22 | |
| S24411-08-06 | 1/2" x 14 | 10 | 6 | 27 | |
| S24411-06-08 | 3/8" x 19 | 12 | 8 | 22 | |
| S24411-08-08 | 1/2" x 14 | 12 | 8 | 27 | |
| S24411-10-08 | 5/8" x 14 | 12 | 8 | 30 | |
| S24411-12-08 | 3/4" x 14 | 12 | 8 | 32 | |
| S24411-10-10 | 5/8" x 14 | 16 | 10 | 30 | |
| S24411-12-10 | 5/8" x 14 | 16 | 10 | 30 | |
| S24411-12-12 | 3/4" x 14 | 19 | 12 | 32 | |
| S24411-16-12 | 1" x 11 | 19 | 12 | 41 | |
| S24411-16-16 | 1" x 11 | 25 | 16 | 41 | |
| S24411-20-20 | 1.1/4" x 11 | 32 | 20 | 50 | |
| S24411-24-24 | 1.1/2" x 11 | 38 | 24 | 60 | |
| S24411-32-32 | 2" x 11 | 50 | 32 | 70 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

BSPT MALE STRAIGHT




| I52II SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|-------------|------|------|---------|----------|
| PROPULSE FITTING PART NO. | E | DN | DASH | S1 | |
| S15211-02-04 | 1/8" x 28 | 6 | 4 | 12 | |
| S15211-04-04 | 1/4" x 19 | 6 | 4 | 14 | |
| S15211-06-04 | 3/8" x 19 | 6 | 4 | 19 | |
| S15211-04-05 | 1/4" x 19 | 8 | 5 | 14 | |
| S15211-06-05 | 3/8" x 19 | 8 | 5 | 19 | |
| S15211-04-06 | 1/4" x 19 | 10 | 6 | 14 | |
| S15211-06-06 | 3/8" x 19 | 10 | 6 | 19 | |
| S15211-08-06 | 1/2" x 14 | 10 | 6 | 22 | |
| S15211-06-08 | 3/8" x 19 | 12 | 8 | 19 | |
| S15211-08-08 | 1/2" x 14 | 12 | 8 | 22 | |
| S15211-12-08 | 3/4" x 14 | 12 | 8 | 27 | |
| S15211-08-10 | 1/2" x 14 | 16 | 10 | 22 | |
| S15211-12-10 | 3/4" x 14 | 16 | 10 | 27 | |
| S15211-08-12 | 1/2" x 14 | 19 | 12 | 22 | |
| \$15211-12-12 | 3/4" x 14 | 19 | 12 | 27 | |
| S15211-16-12 | 1" x 11 | 19 | 12 | 36 | |
| S15211-12-16 | 3/4" x 14 | 25 | 16 | 27 | |
| S15211-16-16 | 1" x 11 | 25 | 16 | 36 | |
| S15211-20-20 | 1.1/4" x 11 | 32 | 20 | 46 | |
| S15211-24-24 | 1.1/2" x 11 | 38 | 24 | 50 | |
| S15211-32-24 | 2" x 11 | 38 | 24 | 65 | |
| S15211-32-32 | 2" x 11 | 50 | 32 | 65 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


BSP BANJO



| 742II SERIES | BOLT SIZE | HOSE | BORE | DIMENSI | ONS (MM) | |
|---------------------------|-----------|------|------|---------|----------|----|
| PROPULSE FITTING PART NO. | | DN | DASH | D | D | Н |
| \$74211-02-03 | 1/8" x 28 | 5 | 3 | 9.9 | 22 | 16 |
| \$74211-04-03 | 1/4" x 19 | 5 | 3 | 13.3 | 24 | 15 |
| \$74211-02-04 | 1/8" x 28 | 6 | 4 | 9.9 | 22 | 16 |
| S74211-04-04 | 1/4" x 19 | 6 | 4 | 13.3 | 24 | 15 |
| \$74211-03-04 | 3/8" x 19 | 6 | 4 | 16.7 | 29 | 20 |
| \$74211-04-05 | 1/4" x 19 | 8 | 5 | 13.3 | 24 | 15 |
| \$74211-06-05 | 3/8" x 19 | 8 | 5 | 16.7 | 29 | 20 |
| S74211-08-05 | 1/2" x 14 | 8 | 5 | 21 | 38 | 25 |
| \$74211-04-06 | 1/4" x 19 | 10 | 6 | 13.3 | 24 | 15 |
| S74211-06-06 | 3/8" x 19 | 10 | 6 | 16.7 | 29 | 20 |
| \$74211-08-06 | 1/2" x 14 | 10 | 6 | 21 | 38 | 25 |
| S74211-06-08 | 3/8" x 19 | 12 | 8 | 16.7 | 29 | 20 |
| \$74211-08-08 | 1/2" x 14 | 12 | 8 | 21 | 38 | 25 |
| S74211-16-08 | 1" x 11 | 12 | 8 | 33.3 | 60 | 42 |
| \$74211-08-10 | 1/2" x 14 | 16 | 10 | 21 | 38 | 25 |
| \$74211-10-10 | 5/8" x 14 | 16 | 10 | 23 | 40 | 27 |
| \$74211-12-10 | 3/4" x 14 | 16 | 10 | 26.5 | 48 | 31 |
| S74211-12-12 | 3/4" x 14 | 19 | 12 | 26.5 | 48 | 31 |
| \$74211-16-12 | 1" x 11 | 19 | 12 | 33.3 | 60 | 42 |
| S74211-16-16 | 1" x 11 | 25 | 16 | 33.3 | 60 | 42 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




SAE CODE 61 3000PSI FLANGE STRAIGHT SAE J516/J518

| 895II SERIES | FLANGE | HOSE | BORE | | DIMENSI | ONS (MM) | |
|---------------------------|--------|------|------|----|---------|----------|------|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | L |
| S89511-08-08 | 1/2" | 12 | 8 | 46 | 30.2 | 24 | 6.73 |
| S89511-12-08 | 3/4" | 12 | 8 | 47 | 38.1 | 31.7 | 6.73 |
| S89511-12-10 | 3/4" | 16 | 10 | 48 | 38.1 | 31.7 | 6.73 |
| S89511-12-12 | 3/4" | 19 | 12 | 48 | 38.1 | 31.7 | 6.73 |
| S89511-16-12 | 1" | 19 | 12 | 51 | 44.5 | 38 | 8 |
| S89511-12-16 | 3/4" | 25 | 16 | 49 | 38.1 | 31.7 | 6.73 |
| S89511-16-16 | 1" | 25 | 16 | 52 | 44.5 | 38 | 8 |
| S89511-20-16 | 1.1/4" | 25 | 16 | 57 | 50.8 | 43 | 8 |
| S89511-16-20 | 1" | 32 | 20 | 53 | 44.5 | 38 | 8 |
| S89511-20-20 | 1.1/4" | 32 | 20 | 58 | 50.8 | 43 | 8 |
| S89511-24-20 | 1.1/2" | 32 | 20 | 68 | 60.3 | 50 | 8 |
| S89511-24-24 | 1.1/2" | 38 | 24 | 68 | 60.3 | 50 | 8 |
| S89511-32-24 | 2" | 38 | 24 | 70 | 71.4 | 62 | 9.53 |
| S89511-32-32 | 2" | 50 | 32 | 70 | 71.4 | 62 | 9.53 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SAE CODE 61 3000PSI FLANGE 45° ELBOW SAE J516/J518



| 8954I SERIES | FLANGE | HOSE | BORE | | DIMI | ENSIONS (| (MM) | M) | |
|---------------------------|--------|------|------|-------|------|-----------|------|------|--|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | Н | L | |
| S89541-08-08 | 1/2" | 12 | 8 | 58.2 | 30.2 | 24 | 19 | 6.73 | |
| S89541-12-08 | 3/4" | 12 | 8 | 58.9 | 38.1 | 31.7 | 26 | 6.73 | |
| S89541-12-10 | 3/4" | 16 | 10 | 70.1 | 38.1 | 31.7 | 26 | 6.73 | |
| S89541-12-12 | 3/4" | 19 | 12 | 77 | 38.1 | 31.7 | 26 | 6.73 | |
| S89541-16-12 | 1" | 19 | 12 | 77 | 44.5 | 38 | 28 | 8 | |
| S89541-16-16 | 1" | 25 | 16 | 85.2 | 44.5 | 38 | 28 | 8 | |
| S89541-20-16 | 1.1/4" | 25 | 16 | 85.2 | 50.8 | 43 | 32 | 8 | |
| S89541-16-20 | 1" | 32 | 20 | 94.5 | 44.5 | 38 | 28 | 8 | |
| S89541-20-20 | 1.1/4" | 32 | 20 | 94.5 | 50.8 | 43 | 32 | 8 | |
| S89541-24-20 | 1.1/2" | 32 | 20 | 95.9 | 60.3 | 50 | 38 | 8 | |
| S89541-24-24 | 1.1/2" | 38 | 24 | 109.9 | 60.3 | 50 | 38 | 8 | |
| S89541-32-24 | 2" | 38 | 24 | 109.9 | 71.4 | 62 | 52 | 9.53 | |
| S89541-32-32 | 2" | 50 | 32 | 129.3 | 71.4 | 62 | 52 | 9.53 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




SAE CODE 61 3000PSI FLANGE 90° ELBOW SAE J516/J518

| 8959I SERIES | FLANGE | HOSE | BORE | | DIMI | ENSIONS (| (MM) | |
|---------------------------|--------|------|------|-------|------|-----------|------|------|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | Н | L |
| \$89591-08-08 | 1/2" | 12 | 8 | 41 | 30.2 | 24 | 40 | 6.73 |
| S89591-12-08 | 3/4" | 12 | 8 | 41 | 38.1 | 31.7 | 58 | 6.73 |
| S89591-12-10 | 3/4" | 16 | 10 | 56.5 | 38.1 | 31.7 | 58 | 6.73 |
| S89591-12-12 | 3/4" | 19 | 12 | 66.2 | 38.1 | 31.7 | 58 | 6.73 |
| S89591-16-12 | 1" | 19 | 12 | 66.2 | 44.5 | 38 | 61 | 8 |
| S89591-12-16 | 3/4" | 25 | 16 | 76.7 | 38.1 | 31.7 | 58 | 6.73 |
| S89591-16-16 | 1" | 25 | 16 | 78 | 44.5 | 38 | 61 | 8 |
| S89591-20-16 | 1.1/4" | 25 | 16 | 78 | 50.8 | 43 | 68 | 8 |
| S89591-16-20 | 1" | 32 | 20 | 91.5 | 44.5 | 38 | 61 | 8 |
| S89591-20-20 | 1.1/4" | 32 | 20 | 91.5 | 50.8 | 43 | 68 | 8 |
| S89591-24-20 | 1.1/2" | 32 | 20 | 91.5 | 60.3 | 50 | 81 | 8 |
| S89591-20-24 | 1.1/4" | 38 | 24 | 108.5 | 50.8 | 43 | 68 | 8 |
| S89591-24-24 | 1.1/2" | 38 | 24 | 109.4 | 60.3 | 50 | 81 | 8 |
| \$89591-32-24 | 2" | 38 | 24 | 109.4 | 71.4 | 62 | 120 | 9.53 |
| S89591-32-32 | 2" | 50 | 32 | 131.8 | 71.4 | 62 | 120 | 9.53 |
| \$89591-40-32 | 2.1/2" | 50 | 32 | 131.8 | 84.1 | 74.4 | 118 | 9.53 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SAE CODE 62 6000PSI FLANGE STRAIGHT SAE J516/J518



| 898II SERIES | FLANGE | HOSE | BORE | | DIME | ENSIONS | (MM) | |
|---------------------------|--------|------|------|----|------|---------|-------|------|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | Н | L |
| S89811-08-08 | 1/2" | 12 | 8 | 47 | 31.8 | 24 | 7.75 | 6.73 |
| S89811-12-10 | 3/4" | 16 | 10 | 51 | 41.3 | 32 | 8.76 | 6.73 |
| S89811-12-12 | 3/4" | 19 | 12 | 51 | 41.3 | 32 | 8.76 | 6.73 |
| S89811-16-12 | 1" | 19 | 12 | 56 | 47.6 | 38 | 9.53 | 6.73 |
| S89811-16-16 | 1" | 25 | 16 | 57 | 47.6 | 38 | 9.53 | 8 |
| S89811-20-16 | 1.1/4" | 25 | 16 | 65 | 54 | 44 | 10.29 | 8 |
| S89811-16-20 | 1" | 32 | 20 | 61 | 47.6 | 38 | 9.53 | 8 |
| S89811-20-20 | 1.1/4" | 32 | 20 | 66 | 54 | 44 | 10.29 | 8 |
| S89811-24-20 | 1.1/2" | 32 | 20 | 75 | 63.5 | 51 | 12.57 | 8 |
| S89811-24-24 | 1.1/2" | 38 | 24 | 75 | 63.5 | 51 | 12.57 | 8 |
| S89811-32-24 | 2" | 38 | 24 | 85 | 79.4 | 67 | 12.57 | 8 |
| S89811-32-32 | 2" | 50 | 32 | 85 | 79.4 | 67 | 12.57 | 9.53 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




SAE CODE 62 6000PSI FLANGE 45° ELBOW SAE J516/J518

| 8984I SERIES | FLANGE | HOSE | BORE | | DIMI | ENSIONS | (MM) | |
|---------------------------|--------|------|------|-------|------|---------|------|-------|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | Н | L |
| \$89841-08-08 | 1/2" | 12 | 8 | 58.9 | 31.8 | 24 | 19 | 7.75 |
| \$89841-12-10 | 3/4" | 16 | 10 | 72.5 | 41.3 | 32 | 26 | 8.76 |
| \$89841-08-12 | 1/2" | 19 | 12 | 74.9 | 31.8 | 24 | 26 | 7.75 |
| S89841-12-12 | 3/4" | 19 | 12 | 79.2 | 41.3 | 32 | 26 | 8.76 |
| \$89841-16-12 | 1" | 19 | 12 | 79.2 | 47.6 | 38 | 28 | 9.53 |
| S89841-16-16 | 1" | 25 | 16 | 90.2 | 47.6 | 38 | 28 | 9.53 |
| \$89841-20-16 | 1.1/4" | 25 | 16 | 96.2 | 54 | 44 | 32 | 10.29 |
| \$89841-20-20 | 1.1/4" | 32 | 20 | 103.8 | 54 | 44 | 32 | 10.29 |
| \$89841-24-20 | 1.1/2" | 32 | 20 | 105.8 | 63.5 | 51 | 38 | 12.57 |
| S89841-24-24 | 1.1/2" | 38 | 24 | 116.2 | 63.5 | 51 | 38 | 12.57 |
| \$89841-32-24 | 2" | 38 | 24 | 125.4 | 79.4 | 67 | 52 | 12.57 |
| \$89841-32-32 | 2" | 50 | 32 | 135.7 | 79.4 | 67 | 52 | 12.57 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


SAE CODE 62 6000PSI FLANGE 90° ELBOW SAE J516/J518



| 8989I SERIES | FLANGE | HOSE | BORE | | DIMI | ENSIONS (| (MM) | |
|---------------------------|--------|------|------|-------|------|-----------|------|-------|
| PROPULSE FITTING PART NO. | SIZE | DN | DASH | Α | С | D | Н | L |
| S89891-08-08 | 1/2" | 12 | 8 | 41 | 31.8 | 24 | 40 | 7.75 |
| S89891-12-10 | 3/4" | 16 | 10 | 56.5 | 41.3 | 32 | 58 | 8.76 |
| S89891-12-12 | 3/4" | 19 | 12 | 66.2 | 41.3 | 32 | 58 | 8.76 |
| S89891-16-12 | 1" | 19 | 12 | 66.2 | 47.6 | 38 | 70 | 9.53 |
| S89891-16-16 | 1" | 25 | 16 | 78 | 47.6 | 38 | 61 | 9.53 |
| S89891-20-16 | 1.1/4" | 25 | 16 | 78 | 54 | 44 | 68 | 10.29 |
| S89891-16-20 | 1" | 32 | 20 | 91.5 | 47.6 | 38 | 61 | 9.53 |
| S89891-20-20 | 1.1/4" | 32 | 20 | 91.5 | 54 | 44 | 68 | 10.29 |
| S89891-24-20 | 1.1/2" | 32 | 20 | 91.5 | 63.5 | 51 | 81 | 12.57 |
| S89891-24-24 | 1.1/2" | 38 | 24 | 109.4 | 63.5 | 51 | 81 | 12.57 |
| S89891-32-24 | 2" | 38 | 24 | 109.4 | 79.4 | 67 | 120 | 12.57 |
| S89891-32-32 | 2" | 50 | 32 | 131.8 | 79.4 | 67 | 120 | 12.57 |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.




STANDARD ORB MALE SOLID SAE J514/J516

| 18211 SERIES | THREAD | HOSE | BORE | DIMENSIONS (MM) | | |
|---------------------------|--------------|------|------|-----------------|--|--|
| PROPULSE FITTING PART NO. | | DN | DASH | S1 | | |
| S18211-04-04 | 7/16" x 20 | 6 | 4 | 14 | | |
| \$18211-05-04 | 1/2" x 20 | 6 | 4 | 17 | | |
| S18211-06-05 | 9/16" x 18 | 8 | 5 | 17 | | |
| \$18211-06-06 | 9/16" x 18 | 10 | 6 | 17 | | |
| \$18211-08-06 | 3/4" x 16 | 10 | 6 | 22 | | |
| \$18211-08-08 | 3/4" x 16 | 12 | 8 | 22 | | |
| S18211-10-08 | 7/8" x 14 | 12 | 8 | 27 | | |
| S18211-10-10 | 7/8" x 14 | 16 | 10 | 27 | | |
| \$18211-12-10 | 1.1/16" x 12 | 16 | 10 | 32 | | |
| S18211-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | | |
| S18211-16-16 | 1.5/16" x 12 | 25 | 16 | 41 | | |

*Dimensions provided are nominal for reference only and may vary based on current supply.

▲ **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

STANDARD ORB MALE SWIVEL SAE J514/J516



| 18211W SERIES | THREAD | HOSE | BORE | DIMENSI | ONS (MM) |
|---------------------------|--------------|------|------|-----------|----------|
| PROPULSE FITTING PART NO. | | DN | DASH | S1 | |
| S18211W-04-04 | 7/16" x 20 | 6 | 4 | 14 | |
| S18211W-06-04 | 9/16" x 18 | 6 | 4 | 17 | |
| S18211W-06-06 | 9/16" x 18 | 10 | 6 | 17 | |
| S18211W-08-06 | 3/4" x 16 | 10 | 6 | 22 | |
| S18211W-08-08 | 3/4" x 16 | 12 | 8 | 22 | |
| S18211W-10-08 | 7/8" x 14 | 12 | 8 | 27 | |
| S18211W-12-08 | 1.1/16" x 12 | 12 | 8 | 32 | |
| S18211W-10-10 | 7/8" x 14 | 16 | 10 | 27 | |
| \$18211W-12-12 | 1.1/16" x 12 | 19 | 12 | 32 | |

^{*}Dimensions provided are nominal for reference only and may vary based on current supply.

[▲] **WARNING:** This product can expose you to chemicals including Lead which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.