

PRESSURE WASHER HOSE (Cold-Water)

ARM-A-FLEX™

It's an undeniable fact: most rubber pressure washer hoses wear from the outside in, rather than the inside out, and in some applications, that happens way too fast. Wooden decks, asphalt roofs/surfaces and concrete can all tear up a hose cover. ProPulse Arm-a-Flex™ boasts a specially engineered ultra-high molecular weight jacket designed to extend hose cover life by up to ten times.

NOT FOR HOT WATER OR STEAM

- › Connectors: SOLxSWV
- › Reinforcement: 2-Layer Wire Braid
- › Cover: UHMWPE Ultra-High Molecular Weight Polyethylene
- › Inner Diameter: 3/8"
- › Working (Max): 4785 PSI
- › Burst (Min) 4:1 Working Pressure
- › Impulse Life: 200,000+
- › Temperature (Max): 212°F

Commercial Arm-A-Flex™ Polyethylene | 3/8" 4785PSI (212°F) (2-Wire Braid)

Item Code	Description
989400258	PW RBR 2WIRE T3 3/8"x50' 4785PSI, SOLxSWV, 2 RED BR (Black)
989400272	PW RBR 2WIRE T3 3/8"x100' 4785PSI, SOLxSWV, 2 RED BR (Black)



PROPULSE™

*Not all listed items have inventory.
Contact your customer service team for product availability.*