

CAR/BAY WASH HOSE (Cold-Water)

CLEANSTREAM™ DROP HOSE

Ideal for self-service carwash applications, Cleanstream™ is the latest patented technology from ProPulse, providing a real upgrade from the standard bay wash drop hose. For the optimal car wash experience and performance, it possesses unique properties such as unmatched UV, ozone, chemical and abrasion resistance, superior flexibility, overall ease of handling and is truly non-marking. The proprietary, matte textured cover is five times more abrasion resistant and up to 30% lighter than its equivalent counterpart, reducing user fatigue.

NOT FOR HOT WATER OR STEAM

- › Connectors: SOLxSOL
- › Reinforcement: 1-Layer Wire Braid
- › Cover: Matte Textured Thermoplastic
- › Inner Diameter: 3/8"
- › Working (Max): 4000 PSI
- › Burst (Min) 3:1 Working Pressure
- › Impulse Life: 200,000+
- › Temperature (Max): 140°F

Cleanstream™ Thermoplastic Drop Hose | 3/8" 4000PSI (140°F) (1-Wire Braid)

Item Code	Description
489400016	PW PLS HYBD BK 3/8"x12' 4000PSI, SOLxSOL, 1SM BR (Matte Black)
489400017	PW PLS HYBD BK 3/8"x15' 4000PSI, SOLxSOL, 1SM BR (Matte Black)
489400018	PW PLS HYBD BK 3/8"x18' 4000PSI, SOLxSOL, 1SM BR (Matte Black)
489400019	PW PLS HYBD BL 3/8"x12' 4000PSI, SOLxSOL, 1SM BR (Matte Blue)
489400020	PW PLS HYBD BL 3/8"x15' 4000PSI, SOLxSOL, 1SM BR (Matte Blue)
489400021	PW PLS HYBD BL 3/8"x18' 4000PSI, SOLxSOL, 1SM BR (Matte Blue)

> NON-MARKING



Not all listed items have inventory. Contact your customer service team for product availability.

⚠ WARNING! This product can expose you to chemicals including nickel which is known to the State of California to cause cancer. For more info visit P65Warnings.ca.gov

