


ISO 18752, 42MPa ISOBARIC HYDRAULIC HOSE



6000 SERIES																	
PROPULSE HOSE PART NO.	HOSE SIZE			HOSE I.D. (MAX)		HOSE O.D. (MAX)		WORKING PRESSURE		PROOF PRESSURE		BURST PRESSURE		BEND RADIUS (MIN)		HOSE WEIGHTS	
	DN	DASH	INCH	MM	INCH	MM	INCH	BAR	PSI	BAR	PSI	BAR	PSI	MM	INCH	KG/M	LBS/ FT
6000 - 12	19	-12	3/4	19.8	0.78	31	1.22	420	6090	840	12180	1680	24360	120	4.72	1.33	0.89
6000 - 16	25	-16	1	26.2	1.03	38	1.5	420	6090	840	12180	1680	24360	150	5.91	1.95	1.31

HOSE CONSTRUCTION:

- › Inner Tube: Oil resistant synthetic rubber
- › Reinforcement: Four or six high tensile steel spirals
- › Cover: Oil, abrasion and weather resistant MSHA approved synthetic rubber

MAIN APPLICATIONS:

- › High pressure, heavy duty, high impulse and high temperature applications

TEMPERATURE RANGE:

- › -40°F / +250°F
- › -40°C / +121°C

FULLY MEETS OR EXCEEDS THE FOLLOWING SPECIFICATION(S):

- › SAE 100R12
- › DIN EN856
- › ISO 18752

NOTE:

- › Not all sizes stocked at all times. Some specifications may vary. Please inquire about availability. ProPulse reserves the right to make any engineering or material changes at any time to our products for enhancement, performance and quality.
- › Available in STANDARD, ROCK and SHIELD cover options.



⚠ WARNING: This product can expose you to chemicals including carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.