

SEWER & JETTER HOSE (Cold-Water)

JETTER LATERAL LINE*

This hose is ideal for consumer and commercial sewer jetters with operating pressures of 4800 PSI or less. ProPulse's jetter hose offers optimum flexibility and lightweight construction.

NOT FOR HOT WATER OR STEAM

Connectors: SOLxSOL or SOLxSWV

Reinforcement: Textile Braid

Cover: Smooth Thermoplastic

>Inner Diameter: 1/8", 1/4" or 3/8" 3/16" (4800 PSI) available on request > Working (Max): 4800 PSI (1/8"), 4400 PSI (1/4") or 4000 PSI (3/8")

> Burst (Min) 2.5:1 Working Pressure

>Impulse Life: 200,000+

> Temperature (Max): 160°F


Jetter Lateral Line & Drain Clean Thermoplastic | 1/8" 4800PSI (160°F) (Textile Braid)

Item Code	Description
686200047	SWR PLS BK 1/8"x25' 4800PSI, SOLxSOL, -04 BUSHING (Black)
686200007	SWR PLS BK 1/8"x50' 4800PSI, SOLxSOL, -04 BUSHING (Black)
686200051	SWR PLS BK 1/8"x100' 4800PSI, SOLxSOL, -04 BUSHING (Black)
686200053	SWR PLS BK 1/8"x200' 4800PSI, SOLxSOL, -04 BUSHING (Black)
686200260	SWR PLS GN 1/8"x50' 4800PSI, SOLxSOL, -04 BUSHING (Green)
686200262	SWR PLS GN 1/8"x100' 4800PSI, SOLxSOL, -04 BUSHING (Green)

Jetter Lateral Line & Drain Clean Thermoplastic | 1/4" 4400PSI (160°F) (Textile Braid)

Item Code	Description
686200032	SWR PLS BK 1/4"x50' 4400PSI, SOLxSWV (Black)
686200012	SWR PLS BK 1/4"x100' 4400PSI, SOLxSWV (Black)
686200010	SWR PLS BK 1/4"x150' 4400PSI, SOLxSWV (Black)
686200020	SWR PLS BK 1/4"x200' 4400PSI, SOLxSWV (Black)
686200050	SWR PLS BK 1/4"x300' 4400PSI, SOLxSWV, REELED (Black)
686200264	SWR PLS GN 1/4"x50' 4400PSI, SOLxSWV (Green)
686200270	SWR PLS GN 1/4"x300' 4400PSI, SOLxSWV, REELED (Green)
686200268	SWR PLS GN 1/4"x200' 4400PSI, SOLxSWV (Green)
686200267	SWR PLS GN 1/4"x150' 4400PSI, SOLxSWV (Green)
686200266	SWR PLS GN 1/4"x100' 4400PSI, SOLxSWV (Green)

> SEE NEXT PAGE FOR 3/8"



* STANDARD 24-HOUR SHIPPING COMMITMENT IS NOT GUARANTEED FOR JETTER HOSE. PLEASE CONTACT YOUR CUSTOMER SERVICE TEAM FOR AVAILABILITY.





SEWER & JETTER HOSE (Cold-Water)

JETTER LATERAL LINE*

This hose is ideal for consumer and commercial sewer jetters with operating pressures of 4800 PSI or less. ProPulse's jetter hose offers optimum flexibility and lightweight construction.

NOT FOR HOT WATER OR STEAM

Connectors: SOLxSOL or SOLxSWV

Reinforcement: Textile Braid

Cover: Smooth Thermoplastic Inner Diameter: 1/8", 1/4" or 3/8" 3/16" (4800 PSI) available on request > Working (Max): 4800 PSI (1/8"), 4400 PSI (1/4") or 4000 PSI (3/8")

>Burst (Min) 2.5:1 Working Pressure

>Impulse Life: 200,000+ > Temperature (Max): 160°F

Jetter Lateral Line & Drain Clean Thermoplastic | 3/8" 4000PSI (160°F) (Textile Braid)

Item Code	Description
686200033	SWR PLS BK 3/8"x50' 4000PSI, SOLxSWV (Black)
686200021	SWR PLS BK 3/8"x100' 4000PSI, SOLxSWV (Black)
686200034	SWR PLS BK 3/8"x150' 4000PSI, SOLxSWV (Black)
686200011	SWR PLS BK 3/8"x200' 4000PSI, SOLxSWV, REELED (Black)
686200035	SWR PLS BK 3/8"x300' 4000PSI, SOLxSWV, REELED (Black)
686200049**	SWR PLS BK 3/8"x400' 4000PSI, SOLxSWV, REELED (Black)
686200159**	SWR PLS BK 3/8"x600' 4000PSI, SOLxSOL, REELED (Black)
686200271	SWR PLS GN 3/8"x100' 4000PSI, SOLxSWV (Green)
686200272	SWR PLS GN 3/8"x150' 4000PSI, SOLxSWV (Green)
686200273	SWR PLS GN 3/8"x200' 4000PSI, SOLxSWV, REELED (Green)
686200275	SWR PLS GN 3/8"x300' 4000PSI, SOLxSWV, REELED (Green)

> SEE PREVIOUS PAGE FOR 1/8" AND 1/4

^{**} Production time for custom hose is 7-10 days from receipt of P.O.





* STANDARD 24-HOUR SHIPPING COMMITMENT IS NOT GUARANTEED FOR JETTER HOSE. PLEASE CONTACT YOUR CUSTOMER SERVICE TEAM FOR AVAILABILITY.

