

## SEWER & JETTER HOSE (Cold-Water)

## **JETTER MAIN LINE\***

These commercial and municipal cleaning hoses, with an operating pressure of 4000 PSI, are designed for truck or trailer mount sewer jetter applications. NOT FOR HOT WATER OR STEAM

Connectors: SOLxSWV

Reinforcement: Textile Braid

Cover: Smooth Thermoplastic

Inner Diameter: 1/2"

Working (Max): 4000 PSI

Burst (Min) 2.5:1 Working Pressure

>Impulse Life: 200,000+

> Temperature (Max): 160°F



**GREEN (GN)** 

## Jetter Lateral Line & Drain Clean Thermoplastic | 3/8" 4000PSI (160°F) (Textile Braid)

Item Code	Description
686200271	SWR PLS GN 3/8"x100' 4000PSI, SOLxSWV (Green)
686200272	SWR PLS GN 3/8"x150' 4000PSI, SOLxSWV (Green)
686200273	SWR PLS GN 3/8"x200' 4000PSI, SOLxSWV, REELED (Green)
686200275	SWR PLS GN 3/8"x300' 4000PSI, SOLxSWV, REELED (Green)

## Jetter Main Line Thermoplastic | 1/2" 4000PSI (160°F) (Textile Braid)

Item Code	Description
686200250	SWR PLS GN 1/2"x50' 4000PSI, SOLxSWV (Green)
686200252	SWR PLS GN 1/2"x100' 4000PSI, SOLxSWV (Green)
686200253	SWR PLS GN 1/2"x200' 4000PSI, SOLxSWV, REELED (Green)
686200095	SWR PLS GN 1/2"x300' 4000PSI, SOLxSWV, REELED (Green)
686200255	SWR PLS GN 1/2"x400' 4000PSI, SOLxSWV, REELED (Green)
686200098	SWR PLS GN 1/2"x500' 4000PSI, SOLxSWV, REELED (Green)
686200256**	SWR PLS GN 1/2"x600' 4000PSI, SOLxSWV, REELED (Green)



\* STANDARD 24-HOUR SHIPPING COMMITMENT IS NOT GUARANTEED FOR JETTER HOSE. PLEASE CONTACT YOUR CUSTOMER SERVICE TEAM FOR AVAILABILITY.

18