


SEWER & JETTER HOSE (Cold-Water)

JETTER MAIN LINE*

These commercial and municipal cleaning hoses, with an operating pressure of 4000 PSI, are designed for truck or trailer mount sewer jetter applications. **NOT FOR HOT WATER OR STEAM**

- › Connectors: SOLxSWV
- › Reinforcement: Textile Braid
- › Cover: Smooth Thermoplastic
- › Inner Diameter: 1/2"
- › Working (Max): 4000 PSI
- › Burst (Min) 2.5:1 Working Pressure
- › Impulse Life: 200,000+
- › Temperature (Max): 160°F



Jetter Main Line Thermoplastic | 1/2" 4000PSI (160°F) (Textile Braid)

Item Code	Description
686200250	SWR PLS GN 1/2"x50' 4000PSI, SOLxSWV (Green)
686200252	SWR PLS GN 1/2"x100' 4000PSI, SOLxSWV (Green)
686200253	SWR PLS GN 1/2"x200' 4000PSI, SOLxSWV, REELED (Green)
686200095	SWR PLS GN 1/2"x300' 4000PSI, SOLxSWV, REELED (Green)
686200255	SWR PLS GN 1/2"x400' 4000PSI, SOLxSWV, REELED (Green)
686200098	SWR PLS GN 1/2"x500' 4000PSI, SOLxSWV, REELED (Green)
686200256**	SWR PLS GN 1/2"x600' 4000PSI, SOLxSWV, REELED (Green)

*** STANDARD 24-HOUR SHIPPING COMMITMENT IS NOT GUARANTEED FOR JETTER HOSE. PLEASE CONTACT YOUR CUSTOMER SERVICE TEAM FOR AVAILABILITY.**

**** Production time for custom hose is 7-10 days from receipt of P.O.**

